

1) LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 12 Township Number T 27 S Range Number R 1 E

County: Sedgewick Distance and direction from nearest town or city street address of well if located within city? 5005 E 21st

2) WATER WELL OWNER: Northeast Health CARE RR#, St. Address, Box #: 5005 E. 21st City, State, ZIP Code: Wichita, KS Board of Agriculture, Division of Water Resources Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the NW section]

4) DEPTH OF COMPLETED WELL: 12.5 ft. ELEVATION: 9 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 9 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 8 in. to 12.5 ft. after 12.5 hours pumping gpm

Est. Yield: 8 gpm Well water was 12.5 ft. after 12.5 hours pumping gpm

Bore Hole Diameter: 8 in. to 12.5 ft. and 12.5 in. to 12.5 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5) TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Threaded X

Blank casing diameter: 2 in. to 2.5 ft. Dia 69 in. to 69 in. Dia

Casing height above land surface: 8 in. weight 69 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 12.5 ft. From 2.5 ft. to 12.5 ft.

GRAVEL PACK INTERVALS: From 2 ft. to 12.5 ft. From 2 ft. to 12.5 ft.

6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 2 ft. From 2 ft. to 2 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 12.5 Clay & Wthrd Shale

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/29/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 581 This Water Well Record was completed on (mo/day/year) 8/10/94 under the business name of Layne, Inc. by (signature) Steven R. Thitchell

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.