1 LOCA	ATION OF W	ATER WELL:	FRACTION CT		rd Form WWC-	Section Number	Township Number	Range Number
Sedgwick			) <u>M</u> R 1/4	SW SE SW	MH 1/4			1
Distance			1 /		#B 1/4	17	т 27 в	R 16 E/W
Distance and direction from nearest town or city street address of well if located within city?								
550 Mims #130 Wichita, Kansas  2 WATER WELL OWNER: STRYKER Sherry								
		DIMINE	R, Sheri					
RR#, ST. ADRESS, BOX#: 550 Mims #130 Nims 5								
	Y, STATE, ZU		a, Kansa				Application Num	aber:
	ATE WELL'S I K" IN SECTIO	N POV.		MPLETED WELL	130		LEVATION:	
1		N I	•	vater Encountered	1	ft.	2 ft.	3 ft.
1		X     WE		VATER LEVEL 2	1 F	. BELOW LAND S	URFACE MEASURED ON mo/day/yr	08/29/1994
j	NW	NE	Pump tes	t data: Well	water was	ft.	after hours pu	ımp <b>i</b> ng gpm
		Est.	Yield	gpm: Well	water was	ft.	after hours pu	ımping gpm
1 Mile	v — —	E Bore	Hole Diameter	<b>12</b> in.	to 130	ft.	and in	ı. to ft.
= '			LL WATER TO	BE USED AS:	5 Public water	er supply	8 Air conditioning 11	l Injection well
١.		SE	1 Domestic	3 Feedlot	6 Oil field w	ater supply	9 Dewatering 12	2 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes No ✗; If yes, mo/day/yr sample was								
S submitted Water Well Disinfected? Yes X No								
TURE OF CASING VISED.								
5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								
2 PV	r	4 ABS		7 Fiberglass	•	DR-26		Threaded
	_		to 110	J	-		& TNI.	
ı	asing Dian	ve land surface 12		ft., Dia weight	in 25	. to lbs./ft.	ft., Dia in.	to ft.
			in., I MATERIAL:	weight 2		7 PVC	Wall thickness or gauge No. 10 Asbestos-ce	.214
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Bra		4 Galvanized steel		6 Concrete tile		9 ABS	12 None used (	• /
			CADE.	F. C		- 1 - 2 - 2	8 Saw cut	11 None (open hole)
1	inous slot	RFORATION OPENIN  3 Mill slot	G ARE:		ızed wrapped e wrapped		9 Drilled holes	11 Hone (open note)
			sal.					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 110 ft. to 130 ft., From ft. to ft.								
l			from		t. to	ft., Fro		o ft.
	GRAV	EL PACK INTERVALS		=	t to 130	ft., Fro		-
lan	OTITE DATE	DDV 1 Noct come	from		t. to	ft., Fro		
Grout Intervals: From 4 ft. to 24 ft. From 95 ft. to 100 ft. From 95								
i .			to 24	ft. From 9	5 ft.	to 100	ft. From	ft. to ft.
What is the nearest source of possible contamination:								Abandon water well
1 Septic tank 4 Lateral			es	• •			l storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool							6 Other (specify below)	
3 Watertight sewer lines 6 Seepage plt 9 Feedyard 13 Insecticide storage None Apparent								
Direction from well? How many feet?								
FROM	1		IOLOGIC LOG		FROM	TO	PLUGGING INT	ERVALS
0	3	topsoil					The second secon	
3	18	clay						
18	28	fine sand						
28	68	fine to me	dium san	d				
68	101	clay						
101	130	fine sand						
							·	
		1-1-02-04-						
<u> </u>								
I								
		· · · · · · · · · · · · · · · · · · ·		Total angular and a second a second and a second a second and a second a second and		<u> </u>		<del></del>
7 (20)	NITED A COST	NDIC			(4)	100		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
was completed on (mo/day/year)								
Under the business name of Harp Well & Pump Service, Inc. by (signature)								
Jane Frederick								
							yarue d	o www.wck