

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE ¼ NW ¼ NE ¼	32	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? Town & Country, 324 West Harry, Wichita, Kansas					
2 WATER WELL OWNER:	Town & Country Markets		01948031 MW-4		
RR#, St. Address, Box # :	P.O. Box 17087		Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :	Wichita, Kansas 67217		Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL... 24.0 ft. ELEVATION: .. Approx.. 1290.0				
	Depth(s) Groundwater Encountered 1... 19.0 ft. 2... ft. 3... ft.				
	WELL'S STATIC WATER LEVEL .. 20.35 ft. below land surface measured on mo/day/yr .. 10/05/94				
	Pump test data: Well water was ... ft. after ... hours pumping ... gpm				
	Est. Yield N/A gpm: Well water was ... ft. after ... hours pumping ... gpm				
	Bore Hole Diameter .. 8.25 in. to .. 24.0 ft., and .. in. to .. ft.				
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only ⑩ Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes..... No... X..... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) ② PVC 4 ABS 14 Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 14 ft. to 24 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 13 ft. to 24 ft., From ft. to ft.					
6 GROUT MATERIAL:					
① Neat cement 2 Cement grout ③ Bentonite 4 Other Grout Intervals: From 0 ft. to 11 ft., From 11 ft. to 13 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage ⑯ Other (specify below) UST 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	1.0	Grass and Topsoil			
1.0	3.5	Dark Brown Lean Clay			
3.5	8.5	Brown, Silty Lean Clay			
8.5	10.0	Gray, Silty Fat Clay			
10.0	24.0	Brown, Fine to Coarse Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/04/94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10-27-94					
under the business name of Terracon Consultants, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					