

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Sedgwick</u>		NE 1/4 NW 1/4 NE 1/4		32		T 27 S		R 1 EW	
Distance and direction from nearest town or city street address of well if located within city?									
<u>Town & Country, 324 West Harry, Wichita, Kansas</u>									
2 WATER WELL OWNER:		Town & Country Markets				01948031 MW-6			
RR#, St. Address, Box # :		P.O. Box 17087				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Wichita, Kansas 67217				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.0 ft. ELEVATION: Approx. 1290.0							
		Depth(s) Groundwater Encountered 1. 19.0 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 20.04 ft. below land surface measured on mo/day/yr 10/05/94							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8.25 in. to 24.0 ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No X							
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded Threaded X	
Blank casing diameter 2 in. to 14 in. Dia		Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		11 Other (specify)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 14 ft. to 24 ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 13 ft. to 24 ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 11 ft. From 11 ft. to 13 ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage		UST	
Direction from well?		How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0.0	0.5	Topsoil							
0.5	8.5	Dark Brown Lean Clay							
8.5	24.0	Brown, Fine to Coarse Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/03/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10/27/94 under the business name of Terracon Consultants, Inc. by (signature)									