			WAT	ER WELL RECORD	Form WWC-	5 KSA 82a	-1212	
1 LOCAT	ION OF WA	TER WELL:	Fraction		Se	ction Number	Township Number	Range Number
				4 SE 4 N		4	T 27 S	R 1 (ÈW
Distance	and direction	n from nearest to	wn or city street	address of well if locate	ed within city?			•
24	25 New	York Ave, 1	Wichita					
2 WATE	R WELL OV	WNER: Unio	on Pacific	Railroad				
RR#, St.	Address, Bo	ox # : Rooi	m 1100, 14:	16 Dodge St.			Board of Agricultu	re, Division of Water Resource:
City, State	e, ZIP Code	: Oma	ha, NE 681	174			Application Number	er:
LOCAT	E WELL'S	OCATION WITH	4 DEPTH OF	COMPLETED WELL	25.3	ft. ELEVA	TION:	
_ ANX.	IN SECTIO	N BOX: N						ft. 3
WELL'S STATIC WATER LEVEL 16.35 ft. TOC measured on mo/day/yr 10-06-94								
	1		Pun	np test data: Well wate	erwas	ft. a	fter hours	pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gp								
•	Bore Hole Diameter8in. to26ft., andin. toin. to							
₹ <b>"</b>	W I I WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
7			1 Domestic	3 Feedlot				12 Other (Specify below)
	SW	SE	2 Irrigation					
1 1	i	1 1	Was a chemical					yes, mo/day/yr sample was sub-
ĭ		\$	mitted			•	ter Well Disinfected? Yes	
TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 Concre			lued Clamped
ــ 1 St	eel	3 RMP (S	R)	6 Asbestos-Cement	9 Other	(specify below	() · · · · · · · · · · · · · · · · · · ·	/elded
(2)P\	/C	4 ABS		7 Fiberglass				hreadedX
		· 2	.in. to 16		in. to		ft., Día	in. to ft.
								e No sch 40
		R PERFORATIO			(7 <b>)</b> PV		10 Asbestos-co	
1 St	eel	3 Stainless	s steel	5 Fiberglass	_	IP (SR)	11 Other (specify)	
2 Brass 4 Galvanized steel				6 Concrete tile 9 ABS			12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:				5 Gauzed wrapped				11 None (open hole)
1 Cc	ontinuous sid	ot (3)M	fill slot	6 Wire wrapped			9 Drilled holes	(3)
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From16								
								ft. toft.
(	GRAVEL PA	CK INTERVALS:						ft. toft.
			From			ft., Fron		ft. to ft.
GROUT	MATERIAL	.: 1 Neat of	cement		(3)Bento			
Grout Inte	rvals: Fro	m 0			1 ft.	to 13	ft., From	ft. toft.
What is th	e nearest so	curce of possible	contamination:			10 Livest	ock pens 14	Abandoned water well
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel s	storage 15	Oil well/Gas well
2 Sewer lines 5 Cess pool				8 Sewage lagoon				Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Unknown								Unknown
Direction f	rom well?			•		How man	_	
FROM	TO		LITHOLOGIC	LOG	FROM	то		G INTERVALS
0	2	Brown sil	t					
2	5	No Recove	ry					
5	10	Black to	brown clay		ŀ			
10	11							
11	12	1						
12	13	Sand						
13	16	Red brown	silt					
16	25	Fine to C	oarse sand	-				
							MW16 - Flux	shmount
							Don Taylor	
			,				2011 14/101	
CONT	ACTORIO 1	OR LANDOWNE	O'S CERTIFICAT	ON: This"		atad (0)	entruoted as (0) stressed	under my jurisdiction and was
1 CONTE	1AU TUR'S (	UNDOWNER	19 CERTICICATI	ON: This water well wa	s ( ) construc	ond this see	dia taua ta tha hart of	under my jurisdiction and was knowledge and belief. Kansas
				•	ell Hecord was		n (mo/day/yr)10-	
	business na		oCore Serv		En '	by (signati		ven copies to Kansas Congament
of Heal	CHONS: Use b	ypewriter or ball point nent. Bureau of Water.	Topeka, Kansas 666	rinivity and <u>Philivi</u> clearly. Ple 20-0001, Telephone: 913-296-5	545. Send one to	WATER WELL ON	the correct answers, send top to NER and retain one for your rec	ree copies to Kansas Department cords.