1 LOCATION OF WATER WELL:	FRACTION AD	Water Well Reco		Section Number		T Down Normalism
	/ / /	W MW SE SI			Township Number	Range Number
Sedgwick	SW 1/4	1/4	BW 1/4	31	T 27 s	R 1E E/W
Distance and direction frem nearest town or city str	reet address of well if loc	cated within city?				
2210 S. Bennett Wichita, Kansas						
		Ita, nume	as			
	DT, Lynn				Board of Agriculture, P.	
	S. Bennet				BOAFU OI Agriculture, 2	Divivsion of Water Resource
CITY, STATE, ZIP CODE: Wichi		as			Application Number	er:
3 LOCATE WELL'S LOCATION WITH 4	DEPTH OF GE	WELL WELL	32	ft. ELI	EVATION:	
AN "Y" IN SECTION BOY.		water Encountered		ft.	2 ft.	3 ft.
• 		_				
		VATER LEVEL 1			RFACE MEASURED ON mo/day/yr	10/05/1994
NWNE	Pump tes	st data: Well	l water was	ft.	after hours pum	ıping gpm
Est	t. Yield	gpm: Well	ll water was	ft.	after hours pum	ıping gpm
)	re Hole Diameter	Br	to	ft.	and in.	to ft.
E Bor	ALL &	A-S		_		
	ELL WATER 10		5 Public wate	•		Injection well
sw sie	1 Domestic	3 Feedlot	6 Oil field wa		9 Dewatering 12 C	Other (Specify below)
	2 Irrigation	4 Industrial	7 Lawn and g	garden only	10 Monitoring well	
	•	eriological sample s	anhmitted to D		J	no/day/yr sample was
e	as a cnemical/bacto ubmitted	eriological sample.	Submines	-		
SU	abmittea					
5 TYPE OF CASING USED:		5 Wrought iron		8 Concrete tile	CASING JOINTS: G	Glued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cem	nent 9	Other (Specify b	velow) V	Velded
2 PVC 4 ABS		7 Fiberglass			•	Threaded X
		J	•			•
Blank casing Diameter 1 1/4 in.	. to	ft., Dia	in.		ft., Dia in.	to ft.
Casing height above land surface 120	0 in.,	weight			Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATIO	ON MATERIAL:			7 PVC	10 Asbestos-ceme	ent
1 Steel 3 Stainless Steel		5 Fiberglass	8	8 RMP (SR)	11 other (specify	()
2 Brass 4 Galvanized steel		6 Concrete tile		9 ABS	12 None used (o)	
				ABS	` •	•
SCREEN OR PERFORATION OPENIN	NG ARE:		uzed wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot		6 Wi	re wrapped		9 Drilled holes	
2 Louvered shutter 4 Key punch	hed				10 Other (specify)	
, , , , , , , , , , , , , , , , , , , ,			rch cut			_
SCREEN-PERFORATION INTERVAL	LS: from	1	ft. to	ft., From	ft. to	ft.
	from	1	ft. to	ft., From	n ft. to	ft.
GRAVEL PACK INTERVAL			ft. to	ft., Fron	•	
GRAVELLI ACAR ANA ZARVA				-		ft.
4 20-4	from		ft. to	ft., Fron		
6 GROUT MATERIAL: 1 Neat cem	ient 2 C	Cement grout	3 Ве	entonite	4 Other bentonite	hole plug
Grout Intervals: From ft	ft. to	ft. From	ft.	to	ft. From	ft. to ft.
What is the nearest source of possible cor		144 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4		10 Livesto		Abandon water well
1 Septic tank 4 Lateral lin		7 Pit privy		11 Fuel st	147	
					130	Oil well/Gas well
2 Sewer lines 5 Cess poo	ol	8 Sewage lag	goon			Other (specify below)
3 Watertight sewer lines 6 Seepage	nit	9 Feedyard		13 insecu	lcide storage	
	P	-			** Fant? E	
	THOLOGIC LOG		FROM	TO	How many feet? 5	
FROM 10	HULOGIC LOC			TO	PLUGGING INTE	RVALS
			0		cement grout	
			6		bentonite hole	
			25		chlorinated san	
		7.7.1		1	UMAVA	W W
					-	
						
					_	
		M			WALL TO SERVICE TO SER	
7 CONTRACTOR'S OR LANDOWNER'S C	ERTIFICATION: Th	is water well was	(1) construct	ed. (2) reconstri	ucted, or (3) plugged under n	nv jurisdiction and
was completed on (mo/day/year)	10/05/	1994	and this rec	ord is true to th	e hest of my knowledge and	helief. Kansas Water
Well Contractor's License No2.	36	This Water Well	Basard was c	ampleted on (m	-Ideathirk 10/0	6/94
Well Colliacion a License 140,	3 11au -	Dis Water Well	Record was c	Ompleted on the	o/day/yr)	N.I
Under the business name ofHari	5V2.***#	"L'milh"" BBY"	Y.T.C.M.V	A.C by (sign	ature)	
Jane Frederick						