1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick	SE 1/4	NE 1/4 NV	V 1/4	17	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?							
1226 Jefferson Wichita, Kansas							
	, Richard						
RRM, ST. ADRESS, BOX #: 1226 Jefferson Board of Agriculture, Divivision of Water Resource							
CITY, STATE, ZIP CODE: Wichita, Kansas 3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 29 ft. ELEVATION:							
3 LOCATE WELL'S LOCATION WITH 4 AN "X" IN SECTION BOX:	DEPTH OF C ON Depth(s) groundwa		29 1	ft. EI ft.	LEVATION:	3 ft.	
	VELL'S STATIC W				URFACE MEASURED ON mo/day/yr	10/25/1994	
NE I	Pump test	_ _	ter was	ft.	after hours pum	1	
	st. Yield	gpm: Well wa	ater was	ft.	after hours pum	1	
	ore Hole Diameter	in. to		ft.	and in.	to ft.	
	ELL WATER 161		Public water		•	njection well Other (Specify below)	
swse	1 Domestic 2 Irrigation		Oil field wat Lawn and ga		9 Dewatering 12 0 10 Monitoring well	Juier (Specify Delow)	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was							
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded							
2 PVC 4 ABS		7 Fiberglass	_			Threaded X	
Blank casing Diameter 1 1/4 in Casing height above land surface 60	n. to	ft., Dia	in.	to lbs. / ft.	ft. , Dia in. Wall thickness or gauge No.	to ft.	
Casing height above land surface 60 in., TYPE OF SCREEN OR PERFORATION MATERIAL:		weight lbs. / 7 PVC			wan thickness of gauge No. 10 Asbestos-cement		
1 Steel 3 Stainless Steel	5 Fiberglass 8 RMP (SR)			11 other (specify)			
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (o	pen hole)	
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous slot 3 Mill slot		6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key punched		7 Torch cut			10 Other (specify)	_	
SCREEN-PERFORATION INTERVALS: from		ft. t	-	ft., Fro		ft.	
GRAVEL PACK INTERVALS: from		ft. to ft. to		ft., Fro ft., Fro		ft.	
from		ft. to		ft., Fre		ft. ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
	ft. to	ft. From	ft. 1		ft. From	ft. to ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines					estock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool		8 Sewage lagoon		46.77 488 4		Oil well/Gas well Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? South	o pro	•			How many feet? 18		
FROM TO LITHOLOGIC LOG			FROM TO		PLUGGING INTE	PLUGGING INTERVALS	
			0	6	cement grout		
			6 20	20	bentonite hole chlorinated san		
			20		CHICIInatea Bai	id and graver	
				1			
				1	Agent agent a common		
		· .					
 							
			<u> </u>				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
was completed on (mo/day/year)		######################################	nd this rec	ord is true to	the best of my knowledge and	belief. Kansas Water 7 / Q 4	
Well Contractor's License No236							
Jane Frederick							
Ī					U		