


WATER WELL RECORD		Section Number		Township Number	Range Number
1 LOCATION OF WATER WELL:		Fraction	SW NW NE E		E/W
County: Sedgwick		SE 1/4 SW 1/4 NW 1/4 E	32	T 27 S	R 1E EW
Distance and direction from nearest town or city street address of well if located within city? 128' W of MTA Property - 21' N of Edge of MTA Bldg. 1825 S. McLean					
2 WATER WELL OWNER: City of Wichita RR#, St. Address, Box #: 455 N. Main City, State, ZIP Code: Wichita, KS 67202 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL... 23 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 17.0 ft. 2. WELL'S STATIC WATER LEVEL 16.16 ft. below land surface measured on mo/day/yr 8/26/94 Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield ... gpm; Well water was ... ft. after ... hours pumping ... gpm Bore Hole Diameter 8 in. to ... ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush Blank casing diameter 2 in. Dia 703 lbs./ft. Wall thickness or gauge No. 154 Casing height above land surface Flush weight 703 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 12 Other (specify) SCREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft. From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 11 ft. to 23 ft. From ... ft. to ... ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 11 ft. to 2 ft. From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? NW How many feet? 300 LITHOLOGIC LOG PLUGGING INTERVALS FROM TO FROM TO 0 3.0 Sand, dark organic 3.0 23 Sand, med. coarse					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1 constructed) (2 reconstructed), or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/26/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10/31/94 under the business name of GST by (signature) Gary Armstrong					

A. Irwin contacted Don Taylor on 11-30-94 about forms being turned in late.