

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE 1/4 SE 1/4 NE 1/4	19	T 27 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 403 N. Seneca, Wichita					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 1298.86			
		Depth(s) Groundwater Encountered 1 15 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 14.80 ft. below land surface measured on mo/day/yr 1-12-95			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield NA gpm: Well water was NA ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 20 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		7 Lawn and garden only 10 Monitoring well MW-5			
		Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <input type="checkbox"/> Clamped <input type="checkbox"/>			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
		7 Fiberglass 10 Asbestos-cement			
Blank casing diameter 2 in. to 10 ft. Dia. in. to ft. Dia. in. to ft.		Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 8 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? SW		How many feet? 50'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Asphalt			
0.5	2.0	Silty Clay (FILL)			
2.0	20	Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-11-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 571 This Water Well Record was completed on (mo/day/yr) 1-16-95 under the business name of BDAT Environmental by (signature) <i>[Signature]</i>					