

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		NE 1/4 NE 1/4 NW 1/4		36		T 27 S		R 1 EW	
Distance and direction from nearest town or city street address of well if located within city? 5401-5515 East Harry (Village Shopping Center), Wichita, Kansas									
2 WATER WELL OWNER:		Resolution Trust Corporation				01958004 MW-4			
RR#, St. Address, Box # :		4900 Main Street				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Kansas City, Missouri 64112				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 40.0 ft. ELEVATION: 1335' AMSL							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 15.7 ft. below land surface measured on mo/day/yr 02/22/95 Pump test data: Well water was N/A ft. after hours pumping gpm Est. Yield N/A gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 40.0 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
		5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X Blank casing diameter 2 in. to 12 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface -3 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40							
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
		SCREEN-PERFORATED INTERVALS: From 12.0 ft. to 37.0 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 9.0 ft. to 40.0 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 7 ft. From 7 ft. to 9 ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0.0	0.2	Asphalt							
0.2	0.9	Concrete							
0.9	3.5	Fill, Sandy Fat Clay							
3.5	33.5	Brown Fat Clay							
33.5	40.0	Olive-Gray Shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/17/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416. This Water Well Record was completed on (mo/day/yr) 5-10-95 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer									