1 LOCATION OF	WATER WELL:	FRACTION	Water Well Rec	ord Form WWC-	5 KSA 82a-1212 Section Number	Township Number	Range Number	
⊢ Sed	gwick	NE 1/4	NW 1/4	SE 1/4		1	, , ,	
				SE 1/4	<u> 4</u>	<u>т</u> 27 _в	R 1E EW	
Distance and direction from nearest town or city street address of well if located within city? 1100 East 21st Wichita, Kansas								
			<u>hita, Kan</u>	sas				
2 WATER WEI		AL REFINI						
RR#, ST. ADRI		t Street			Board of Agriculture, Divivsion of Water Resource			
CITY, STATE,		ta, Kans			67214	Application Number	r:	
3 LOCATE WELL AN "X" IN SEC	'S LOCATION WITH		MPLETED WELL			VATION:		
	N	Depth(s) grounds	vater Encountered	1	ft.	2 ft.	3 ft.	
1 1 1	W	ELL'S STATIC V	VATER LEVEL 3	Լ5 Ի	. BELOW LAND SUR	FACE MEASURED ON mo/day/yr	05/12/1995	
N	WNE	Pump tes	st data: Well	water was	ft. a	fter hours pum	ping gpm	
	Est	. Yield	gpm: Well	l water was	ft. a	fter hours pum	ping gpm	
M M M M M M M M M M	E Boi	re Hole Diameter	8 in.	to 30	ft.	and in.	to ft.	
-	^ WI	ELL WATER TO	BE USED AS:	5 Public water	r supply 8	Air conditioning 11 Is	rjection well	
ss	w	1 Domestic	3 Feedlot	6 Oil field wa	iter supply 9	Dewatering 12 O	ther (Specify below)	
		2 Irrigation	4 Industrial	7 Lawn and g	garden only 10	Monitoring well		
	Ws	as a chemical/bact	eriological sample s	submitted to D	epartment? Yes	No X ; If yes, m	o/day/yr sample was	
S submitted Water Well Disinfected? Yes No X								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								
2 PVC	4 ABS		7 Fiberglass		•	T	hreaded X	
Blank casing Di	ameter 2 in.	to 9	ft., Dia	in.	to	ft., Dia in.	to ft.	
		_	,			Vall thickness or gauge No.	.154	
Casing helght above land surface flush in., welght .703 lbs. / ft. Wall thickness or gauge No154 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify))	
2 Brass	4 Galvanized steel		6 Concrete tile		ABS	12 None used (op		
BC								
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 saw cut 11 None (open note) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 I ownered shotters A Vision and all								
/ Torch cut								
SCREEN-I ERI	CORATION INTERVAL			t. to 29	ft., From	ft. to	ft.	
CD.	THE DACK INTERNAL	from		ft. to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 7				ft. to 29	ft., From ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals	_	. to 2						
	rest source of possible cor		ft. From 2	ft.	to 7 10 Livestocl	ft. From	ft. to ft.	
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel stor		14 Abandon water well	
			8 Sewage lagoon		12 Fertilize	130	15 Oil weil/Gas weil 16 Other (specify below)	
5 ccas poor				13 Insectici	de etemen			
o seepage pit relinery								
Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							DVALC	
0 14	dark gray			FROM	+ 10-+	PLUGGING INTER	(VALS	
14 16					 			
16 30	sandy clay							
10 30	fine to co	oarse san	ıa					
					+			
						247		
						1.000 1.000		
			1000			LAVAPOT		
		1_131						
						119.21		
 								
						40.		
\vdash								
		1.0.11.010	1.504					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No236								
Under the business name of Harp Well & Pump Service, Inc. by (signature)								
Jane Frederick								