1 LOCA	TION OF WA	TER WELL:	FRACTIO	N	wa	ter Well Rec	ord Form	wwc-s	Section Number	Township Number	Range Number
尸	Sedgv	rick	SE	1/4	NW	1/4	SE	1/4	4	T 27 s	p 1E FAW
Distance		frem nearest town or city street					~-		_	1 2 3	R IE E/W
1100 East 21st Wichita, Kansas											
	TER WELL					Kan	sas				
Ľ	ST. ADRESS,	COADIA								Board of Agriculture.	Divivsion of Water Resource
ı	, STATE, ZIP					eet			67214	Application Numb	
			DEPTH OI		-	D WELL	- 3	3		EVATION:	VI.
200	" IN SECTIO	V DOV.					, J	3	ft.	2 ft.	3 ft.
Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.  WELL'S STATIC WATER LEVEL 13.42 FT. BELOW LAND SURFACE MEASURED ON mod/day/yr 05/02/1995											
		WE		np test			LJ.¥Z l water w			after hours pur	
'	<b>NW</b>	NE	Yield	np cese	gpm:		l water w			after hours pur	
1₹ Mile Mile			Hole Dian	neter	12	in.	to 3		ft.	and in.	to ft.
\ \ \ \			L WATER				_	_			Injection well
l .	1	-/!	1 Domestic		3 Feed						Other (Specify below)
I	SW		2 Irrigation		4 Indus	strial	7 Lawn	and g		0 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes  No X ; If yes, mo/day/yr sample was											mo/day/yr sample was
S submitted Water Weli Disinfected? Yes X No											
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped											
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded										•	
2 PVC 4 ABS 7 Fiberglass Threaded X											
·	 asing Diam		to 18		ft.,	Dia		in.	to	ft., Dia in.	to ft.
	•	ve land surface 24		in.,	,		3.68			Wall thickness or gauge No.	.280
TYPE OF SCREEN OR PERFORATION MATERIAL:  7 PVC  10 Asbestos-cement											
1 Ste	el	3 Stainless Steel			5 Fiber	glass		8	RMP (SR)	11 other (specia	<b>'y</b> )
2 Bra	SS	4 Galvanized steel			6 Concr	rete tile		5	O ABS	12 None used (c	pen hole)
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
1 Conti	inous slot	3 Mill slot				6 Wi	re wrappe	d		9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATION INTERVALS: from 18 ft. to 33 ft., From ft. to ft.											
from ft. to ft., From ft. to									ft.		
GRAVEL PACK INTERVALS: from 1								3	ft., From		
			fron				ft. to		ft., Fron		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug											
Grout Intervals: From 4 ft. to 14.5 ft. From ft. to ft. From 14.5 ft. to 16 ft.											
What is the nearest source of possible contamination:									10 Livesto		Abandon water well
1 Septic tank 4 Lateral lines			es	7 Pit privy				11 Fuel ste	13	Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon					12 Fertilizer storage 13 Insecticide storage		Other (specify below)
ı	ertight sew	I 8- I-	it		9 F	Feedyard			15 Insection	cide storage ref	inery
	on from we		101 05	1.00						How many feet?	201111
FROM O	16	_	OLOGIC	LOG			FR	OM	TO	PLUGGING INTI	KVALS
16	24	clay fine to me	41,		1						
24	33	medium to									
44	33	MEGIUM TO	coars	e Së	Ind		-			Application of the second of t	
		****									
									<del>                                     </del>		
	<b>1</b>								<del>                                     </del>		
								-	++		
			•••								
1											
	<b>†</b>								+		
									- <del> </del>		
7 (20)	J	L					44)				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)											
Well Contractor's License No2.3.6											
Under the business name of Harp Well & Pump Service, Inc., by (signature)											
										lane d	Frederick
										1	