


1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SW 1/4 SE 1/4	Section Number 4	Township Number T 27 S	Range Number R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? 1100 East 21st Street Wichita, Kansas				
2 WATER WELL OWNER: COASTAL REFINERY		Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #: 1100 East 21st Street		Application Number:		
CITY, STATE, ZIP CODE: Wichita, Kansas 67214				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 30 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 13.12 FT. BELOW LAND SURFACE MEASURED ON 04/17/1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm : Well water was ft. after hours pumping gpm Bore Hole Diameter 20 in. to 30 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recov. Well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No		
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded X 7 Fiberglass Threaded Blank casing Diameter 14 in. to 14 ft., Dia in. to ft., Dia 14 in. to 27-30 ft. Casing height above land surface 24 in., weight 54.57 lbs. / ft. Wall thickness or gauge No. .375 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 14 ft. to 27 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 11 ft. to 30 ft., From ft. to ft. from ft. to ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 0 ft. to 9 ft. From ft. to ft. From 9 ft. to 11 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) refinery Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS				
0 13.5 tan clay				
13.5 27 fine to medium sand and fine gravel				
27 30 clay				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/17/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 05/08/95 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>				