1 LOCA	TION OF W	ATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick		wick	NE 1/4	SE 1/4 S	E 1/4	4	т 27 s	R 1E EW	
Distance and direction frem nearest town or city street address of well if located within city?									
1100 East 21st Street Wichita, Kansas									
	TER WELL		L REFINE		ca, nai	ISas			
	ST. ADRESS	CORDIN	ast 21st				Board of Agriculture, I	Divivsion of Water Resource	
1	, STATE, ZII		ast 21st a, Kansa			67214	•	Application Number:	
					30	67214 ft. ELEV		#:	
Ocate well's location with A DEPTH OF COMPLETED WELL 30 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.									
WELL'S STATIC WATER LEVEL 16.09 FT. BELOW LAND SURFACE MEASURED ON 100/day/yr 04/20/1995									
		WE	Pump test	:	ater was			. 1	
l '	NW	NE	Yield		ater was vater was		fter hours pun fter hours pun		
1 Mile Mile			Hole Diameter	SP	to 30	n. a ft.	and in.	iping gpm to ft.	
ΣA		P	LL WATER TO		Public water	_		njection well	
١.			1 Domestic		Oil field wat			Other (Specify below)	
	SW		2 Irrigation	4 Industrial 7	Lawn and ga	rden only 10	Monitoring well Re	cov. Well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was									
S submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded X									
2 PVC 4 ABS 7 Fiberglass Threaded									
Blank casing Diameter 14 in. to 14 ft., Dia in. to ft., Dia 14 in. to 27 • 30 ft.									
Casing height above land surface 24 in., weight 54.57 ibs./ft. Wall thickness or gauge No 375									
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 14 ft. to 27 ft., From ft. to ft.									
from ft. to						ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 11				ft. to 30		ft., From	ft. to	ft.	
from ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 0 ft. to 9 ft. From ft. to ft. From 9 ft. to 11 ft.									
What is the nearest source of possible contamination:						10 Livestocl		Abandon water well	
1 Septic tank 4 Lateral li			es	7 Pit privy		11 Fuel stor	131	Oil well/Gas well	
ŀ	r lines	5 Cess pool		8 Sewage lagoon		12 Fertilize	J	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery									
Direction FROM	n from we	<u> </u>	IOLOGIC LOG		EDCM	TO I	How many feet?	DVALC	
O C	14	tan clay	OLOGIC LOG		FROM	то	PLUGGING INTE	KVALS	
14	27	fine to co	arce can	d and					
	"	gravel	arec sall	u anu					
27	30	clay		7/4					
		- vanj			†			A Section and the second	
L			7011						
				- W-W			-11/	-1	
			NATA CONTRACTOR OF THE PARTY OF						
				·					
			770				70.71.11		
				917					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Well Contractor's License No23.6									
Under the business name of Harp Well & Pump Service, Inc by (signature)									
				_		J. 3		rederick	
june o account									