				Water Well Reco	rd Form WWC-5				
		ATER WELL:	FRACTION			Section Number	Township Number	Range Number	
	Sedg		SW 1/4		SE 1/4	4	<u>т 27 s</u>		
Distance and direction frem nearest town or city street address of well if located within city?									
1100 East 21st Street Wichita, Kansas									
2 WA	TER WELL	OWNER: COAST	AL REFINE	ERY					
RR#, ST. ADRESS, BOX #: 1100 East 21st Street Board of Agriculture, Divivision of Water Resource									
СІТЗ	, STATE, ZIJ		ta, Kansa			67214	Application Numbe	r:	
3 LOCA	TE WELL'S I			MPLETED WELL	28	ft. EL	EVATION:		
	" IN SECTIO		Depth(s) ground	vater Encountered	1	ft.	2 ft.	3 ft.	
l t			ELL'S STATIC W		9.99 FT	. BELOW LAND SU	RFACE MEASURED ON mo/day/yr	04/20/1995	
			Pump tes		water was	ft.	after hours pum		
	NW	NE F.st.	Yield	gpm: Well	water was	ft.	after hours pum		
Mile M			e Hole Diameter	20 in.	to 28	ft.	and in.	to ft.	
Į Ž ₩			LL WATER TO		5 Public wate			njection well	
			1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)	
	SW	S#E	2 Irrigation	4 Industrial	7 Lawn and s			cov. Well	
		X				•			
•	L	0		eriological sample s	submitted to D	-		no/day/yr sample was	
submitted water wen Disintected : Yes X No									
	5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped								
1 Stee	_	3 RMP (SR)		6 Asbestos-Cem	ent 9	Other (Specify	,	Velded X	
2 PV	2	4 ABS		7 Fiberglass			1	Threaded	
Blank c	asing Dian	neter 14 in.	to 19	ft., Dia	in.		ft., Dia <b>14</b> in.	to 25-28 ft.	
-	Casing height above land surface 24 in., weight 54.57 lbs. / ft. Wall thickness or gauge No 375								
		EN OR PERFORATIO	N MATERIAL:	f Dibanataan		7 PVC	10 Asbestos-cem		
1 Ste		3 Stainless Steel		5 Fiberglass		8 RMP (SR)	11 other (specify	()	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							pen hole)		
SCREE	N OR PE	RFORATION OPENIN	NG ARE:	5 Gai	uzed wrapped		8 Saw cut	11 None (open hole)	
1 Conti	nous slot	3 Mill slot		6 Wir	re wrapped		9 Drilled holes		
2 Louve	red shutte	er 4 Key punch	ed	7 Tor	ch cut		10 Other (specify)		
SCREE	SCREEN-PERFORATION INTERVALS: from 19 ft. to 25 ft., From ft. to ft.								
from ft. to ft., From ft. to ft.									
GRAVEL PACK INTERVALS: from 17				-			•		
			from		ft. to	ft., Fro		ft.	
6 GRO	OUT MAT	ERIAL: 1 Neat ceme	ent 2	Cement grout	3 Be	ntonite	4 Other bentonite	hole plug	
Grout I	itervals:	From O ft.	• to 15.75	ft. From	ft.	to	ft. From 15.75		
	What is the nearest source of possible contamination:				10 Livesto			bandon water well	
	ic tank	4 Lateral lin		7 Pit privy	7 Pit privy 11 Fuel:		torage 15 (	Oil well/Gas well	
2 Sewe				8 Sewage lag			-	Other (specify below)	
	5 6635 1001				• •		icide storage refinery		
Direction from well?         How many feet?           FROM         TO         LITHOLOGIC LOG         FROM         TO         PLUGGING INTERVALS							RVALS		
0		tan clay			- ROM	+ * +			
18.75		fine to co	area cer	d and					
		gravel	arse sal				······································		
25	20			·					
25	28	clay						·	
							- 1411		
							and the second second		
						_			
7 CO	TRACTO	R'S OR LANDOWNER'S C	ERTIFICATION: Th	is water well was	(1) construct	ed. (2) reconstr	ructed, or (3) plugged under n	ny jurisdiction and	
<sup>7</sup> CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
Well C	Well Contractor's License No								
Under	Under the business name of HARD NOLL & PUMP Service, INC by (signature)								
I	Jane Frederick								

Jane	Frederick
------	-----------