Loca	TION OF WA	TER WELL:	FDA	CTION	Wa	ter Well Reco	ord Form WWC	-5 KSA 82a-1212 Section Number		Range Number	
ப									3311224 111223	1	
	Sedgv		N1		NE	1/4	SE 1/4	4	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?											
_		st 21st S				Wich	<u>ita, K</u>	ansas			
WATER WELL OWNER: COASTAL REFINERY											
RR#, ST. ADRESS, BOX#: 1100 East 21st Street Board of Agriculture, Divivision of Water Resource										ivivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kansas 67214 Application Number:											
	E WELL'S I				MPLETE				LEVATION:		
A	ENSECTIO	N BOA.	- '	. •	vater Enc		1	ft.	2 ft.	3 ft.	
WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mod/day/yr 04/20/199										04/20/1995	
Pump test data: Well water was ft. after hours pumping g										iping gpm	
ي ا	1		Est. Yield		gpm:	Well	l water was	ft.	after hours pum	ıping gpm	
M M M	-	1 1	Bore Hole		12	in.	to 29	ft.	and in.	to ft.	
"		1	WELL WA				5 Public was		•	njection weli	
۱ ،	sw		1 Dom		3 Feed			vater supply	•	Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Recov. Well										
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was										
Submitted water wen Dismected: Yes X NO											
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped											
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded X											
2 PVC 4 ABS 7 Fiberglass Threaded											
Blank casing Diameter 6 in. to 17 ft., Dia in. to ft., Dia 6 in. to 26-29 ft.											
Casing height above land surface 24 in., weight 18.97 lbs./ft. Wall thickness or gauge No280 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement											
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)											
2 Bras	_	4 Galvanized stee			6 Conc	_		9 ABS	,		
DO-11											
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes											
A LA MARINE MARI											
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATION INTERVALS: from 16 ft. to 26 ft., From ft. to ft.											
from						ft. to		ft., Fr		ft.	
GRAVEL PACK INTERVALS: from 14					4	 -		ft., Fr		ft.	
clope	TIT BAARN	No. 1 No.		from	<u> </u>		ft. to	ft., Fr			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug											
Grout Intervals: From 0 ft. to 12					ft.	ft. From ft. to			ft. From 12 stock pens 14 A	ft. to 14 ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines					7			etoman			
						8 Sewage lagoon				15 Oil well/Gas weli 16 Other (specify below)	
12 Inscalled a storage								` '			
Swaterught sewer mes 6 Seepage plt 9 reedyard relinery										.nery	
Direction from well? How many feet? FROM TO PLUGGING INTERVALS									RVALS		
0	14	tan clay									
14	29	medium f		and							
			*								
			sar.							***	
						-					
			y 4								
7 CON	TRACTO	R'S OR LANDOWNER	r'S CERTIFIC	ATION: Th	nis water	well was	(1) construc	ted, (2) recons	tructed, or (3) plugged under n	ny jurisdiction and	
was co	mpleted	on (mo/day/year)	Ω	4 <i>/</i> .20/	.1 <u>995</u> .		and this re	cord is true to	the best of my knowledge and	belief. Kansas Water	
Well C	ontractor	's License No	<u> 236 </u>		This Wa	ter Well	Record was	completed on	(mo/day/yr)Ω5./.Ω	8/95	
Under the business name of Harp Well & Pump Service Inc by (signature)											
Jane Frederick											