1 LOCATION OF WATER WELL:			FRACTION	Water Well Reco	rd Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number
Sedgwick		SW 1/4	NE 1/4	SE 1/4	4	T 27 s	R 1E EW	
Distance and direction frem nearest town or city street address of well if located within city?								
1100 East 21st Street Wichita, Kansas								
	TER WELL		TAL REFINE					
	RRW, ST. ADRESS, BOX#: 1100 East 21st Stree				Board of Agriculture, Divivsion of Water Resource			
CITY, STATE, ZIP CODE: Wichita, Kansas 3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL						67214 ft. ELE	Application Number	r:
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 36 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.								
l t		- 	WELL'S STATIC W		_		FACE MEASURED ON mo/day/yr	04/25/1995
	NW	NE	Pump test		water was	ft. a	fter hours pum	
و			Est. Yleld	gpm: Well	water was	ft. a	ofter hours pum	ping gpm
1Mile	/ 		Bore Hole Diameter	12 in.	to 36	ft.	and in.	to ft.
"			WELL WATER TO F	BE USED AS: 3 Feedlot	5 Public wate		-	njection well Other (Specify below)
	sw		2 Irrigation	4 Industrial	6 Oil field wa 7 Lawn and g		Dewatering 12 C Monitoring well	ther (specify below)
			Was a chemical/bacte	riological sample s			-	o/day/yr sample was
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								
2 PVC 4 ABS 7 Fiberglass Threaded X								
Blank casing Diameter 6 in. to 18 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 24 in., weight 3.68 lbs./ft. Wall thickness or gauge No								
Casing height above land surface 24 in., weight 3.68 lbs./ft. Wall thickness or gauge No								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass 4 Galvantzed steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 18 ft. to 36 ft., From ft. to ft. from ft. to ft.								
from GRAVEL PACK INTERVALS: from 14					ft. to ft. to 36		ft. to ft. to	ft. ft.
			from		t. to			î.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 4 ft. to 12 ft. From ft. to ft. From 12 ft. to 14 ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well								
1 Septic tank 4 Lateral l				7 Pit privy		11 Fuel sto		bandon water well Dil well/Gas well
2 Sewer lines 5 Cess 1				8 Sewage lagoon		12 Fertilize	130	Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery								
Direction from well? How many feet?								
FROM O	15	clay	ITHOLOGIC LOG		FROM	то	PLUGGING INTER	(VALS
0 15 20	20		nedium sand	a	47-24	1 - 1	THE PARTY OF THE P	1 1 Land
20	25	clay						
25	36	fine to r	nedium sand	đ				Annual Burnard
			Di					
						+		
					1			
				77.0				
7 CONTRACTORIS ON A NORMANDA CONTRACTORIS ON This was a second of the se								
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Well Contractor's License No236 This Water Well Record was completed on (mo/day/yr)								
Under the business name of Harp Well & Pump Service, Inc by (signature)								
Jane Frederick								