1 LOCATION OF WATER WELL:			FRACTION	N.	Water Well Re	cord Form W		A 82a-1212 Hon Number	Township Numb	pr	Range Number	_
Sedgwick			NW	1/4 NE	E 1/4	SE 1	/4	4	т 27		P 1E FAV	
Distance and direction frem nearest town or city street address of well if located within city?												
1100 East 21st Street Wichita, Kansas												
	TER WELL		AL REF	TNEDV	WICI	iita,	Nalisa	15				
_	ST. ADRESS		East 2		treat				Beard of	Agriculture, Di	vivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kansas								214	Application Number:			
		OCATION WITH 4						EVATION:				
	" IN SECTIO		Depth(s) gro				, 10	. ELL ft.	2	ft.	3 ft.	
l t			VELL'S STAT				FT. BELO		RFACE MEASURED ON		04/25/199	
				np test data		12.92 Il water was				hours pumi		- 1
l '	NW	NE	st. Yield	-		n water wa: ell water wa					· • • • • • • • • • • • • • • • • • • •	pm
y M			ore Hole Diam	gpi leter 1	11. we 12 in.	to 36	-	ft.	and	hours pumj in.		pm t.
≅ w			ELL WATER				, vater supp	_	8 Air conditioning		to fi njection w ell	٦
		"	1 Domestic		eedlot		i water su	•	9 Dewatering		ther (Specify below)	
	- sw	SE	2 Irrigation		ndustrial	7 Lawn a			0 Monitoring well		(- F ,	
			J		aical sample			_	•	· If ves me	o/dav/vr samnle was	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ▼ No												
TVDE OF CASING LISED.												
5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamp 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded												
2 PVC	7	4 ABS			iberglass		, Juic	. (Specify De				
	_ asing Diam		n. to 16		· ·		in 4		a Di-	-	A	
	-	ve land surface 24		in.,	,	3.68	in. to		ft. , Dia Wall thickness or ga	in. uge No	to ft. .280	
		N OR PERFORATION			weight	3.00	7 PVC			uge 140. bestos-ceme		
1 Ste	el	3 Stainless Steel		5 Fi	iberglass		8 RMF	_	11 ot	her (specify))	ļ
2 Bra	55	4 Galvanized steel		6 Cc	oncrete tile		9 ABS		12 No	ne used (op	en hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)												e)
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes												
2 Louve	red shutte	r 4 Key pund	ched		7 To	rch cut			10 Other (speci	fy)		
SCREEN-PERFORATION INTERVALS: from 16 ft. to 36 ft., From ft. to ft.												
			from			ft. to		•		ft. to		ft.
1	GRAVI	EL PACK INTERVA		14		ft. to 36		ft., From ft., From		ft. to		ı
from					ft. to			ft., From		ft. to	1	ft. ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug												
Grout Intervals: From 4 ft. to 12 ft. From ft. to ft. From 12 ft. to 14 ft.												.
What is the nearest source of possible contamination:					ic riom			10 Livestock pens		14 Abandon water well		"
1 Septic tank 4 Lateral lines				7 Pit privy			11 Fuel storage		15 Oil well/Gas well			
2 Sewer lines 5 Cess pool				8 Sewage lagoon			12 Fertilizer storage		16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit								13 Insection	cticide storage refinery			
li .	n from wel	1 0	F		•				How many feet?			
FROM	TO		THOLOGIC	LOG		FRO	M	TO		ING INTER	IVALS	
0	16	clay										
16	20	fine to m	edium s	sand								
20	25	clay										
25	36	fine to m	edium s	sand								
		To the state of the November A. U. a consider a consideration										
									,,			_

							_					\dashv
							_					-
							-					\dashv
_												
⁷ CON	TRACTO	R'S OR LANDOWNER'S	CERTIFICATION	: This wat	ter well was	s (1) <u>constr</u>	ucted, (2)) reconstru	cted, or (3) plugge	ed under m	y jurisdiction and	
											belief. Kansas Wate	er
Well C	ontractor	's License No		This	Water Well	Record wa	s comple	eted on (mo	o/day/yr)	ກ ສ.γ.۲۵	l./	
Under	the busin	ess name ofHax	.ħưa.ㅠㅠ.	x £.un	irvex	XY&8'\'''	SA.	by (signa		T	/ 0	
1									yа	me J'	rederick	- 1