1 LOCATION OF WATER WELL:			FRACTION	<del></del>	Water Well Rec	ord Form WWC-	5 KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick		SE	1/4 NV	<b>T</b> 1/4	SE 1/4	4	T 27 s	R 1E EW		
Distance and direction frem nearest town or city street address of well if located within city?										
1100 East 21st Street Wichita, Kansas										
	TER WELL			INERY		2047 110		1 <b>1111</b>		
RR#,	ST. ADRESS				treet			Board of Agriculture, l	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kansas								Application Number:		
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 35 ft. ELEVATION:										
AN "X" IN SECTION BOX:  Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.										
l t		WE	LL'S STAT	IC WATE	R LEVEL	13.27 F	T. BELOW LAND SU	URFACE MEASURED ON mo/day/yr	04/26/1995	
	NW	NE	Pun	ıp test data	: Wel	water was	ft.	after hours pun	nping gpm	
l .	<b>NW</b>	1 -!- 1 1	Yleld	gpi	m: Wei	i water was	ft.	after hours pur		
Mile M	/	E Bore	Hole Diam	eter ]	. 2 in.	to 35	ft.	and in.	to ft.	
= "		WE	LL WATER			5 Public water	er supply	8 Air conditioning 11	Injection well	
١.			1 Domestic	3 F	eedlot	6 Oil field w	ater supply	9 Dewatering 12	Other (Specify below)	
	SW		2 Irrigation	4 II	ndustrial	7 Lawn and	garden only	10 Monltoring well		
			a chemical	/bacteriolo	gical sample	submitted to D	epartment? Yes	No X; If yes, 1	no/day/yr sample was	
S submitted Water Well Disinfected? Yes X No										
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped										
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									Welded	
2 PVC 4 ABS 7 Fiberglass Threaded X										
Blank casing Diameter 6 in. to 18 ft., Dia in. to ft., Dia in. to ft.										
Casing height above land surface 24 in., weight 3.68 lbs. / ft. Wall thickness or gauge No 280 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
l .			N MATERIA		hawalaaa		7 PVC	10 Asbestos-cen		
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)										
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)										
1		RFORATION OPENIN	G ARE:			uzed wrapped		8 Saw cut	11 None (open hole)	
	inous slot	3 Mill slot			6 Wi	re wrapped		9 Drilled hoies		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATION INTERVALS: from 18 ft. to 35 ft., From ft. to ft.										
from					ft. to		ft., Fron	n ft. to	ft.	
GRAVEL PACK INTERVALS: from 16					ft. to 35		ft., Fro	m ft. to	ft.	
from ft. to ft., From ft. to									ft	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From 14 ft. to 16 ft.										
What is the nearest source of possible contamination:					7 Dis		10 Livesto		Abandon water well	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel st		Oll well/Gas well		
2 Sewer lines 5 Cess pool					8 Sewage la	-			Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery									inery	
FROM	n from we		IOLOGIC I	LOG		FROM	то	How many feet? PLUGGING INTE	PVALS	
0	18	clay	iologic i	LOG		FROM	1 10	FLUGGING INTE	AVALS	
18	25	fine to me	dium s	sand						
25	35	medium to			1			A. L.		
								•		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and										
was completed on (mo/day/year)										
Well Contractor's License No236										
Under the business name of Harp Well & Pump Service by (signature)										
Jane Frederick										
								//		