Loca	TION OF W	TED WELL.	FRACTION	Wat	ter Well Reco	rd Form WWC-	Section Number	T		Range Number	
LOCATION OF WATER WELL: Sedqwick			NW	• • •	CP	1 .			110		
Sedgwick SE 1/4 N Distance and direction frem nearest town or city street address of well if located w						SE 1/4	4	т 27	<u>s</u>	R 1E EW	
1100 East 21st Street Wichita, Kansas											
	TER WELL		<u>reet</u> AL REFIN		WICH:	Ita, Ka	insas				
	ST. ADRESS,		East 21s		ee+			Board	of Agriculture, Di	vivsion of Water Resource	
1	Y, STATE, ZIP		ta, Kans					Application Number:			
3 LOCA	TE WELL'S I	OCATION WITH 4	DEPTH OF C		D WELL	34		LEVATION:			
AN "X	" IN SECTIO	N BOX:	Depth(s) groun	dwater Enco	untered	1	ft.	2	ft.	3 ft.	
1 1		W	ELL'S STATIC	WATER LI	EVEL 1	3.02 F	T. BELOW LAND S	SURFACE MEASURED	ON mo/day/yr	04/26/1995	
1 1	NW	NE	Pump	test data:	Well	water was	ft.	after	hours pum	ping gpm	
۰		Est	. Yield	gpm:	Weli	water was	ft.	after	hours pum	ping gpm	
1Mile	v 	E Bor	e Hole Diamete	r 12	m.	to 34	ft.	and	in.	to ft.	
-			LL WATER T			5 Public wat		8 Air conditioning	·	njection well	
1 1	sw	X	1 Domestic	3 Feed		6 Oil field w	•••	9 Dewatering		ther (Specify below)	
			2 Irrigation	4 Indu		7 Lawn and	•	10 Monitoring well			
'	<u> </u>	6		cteriologica	l sample s	ubmitted to D	epartment? Yes			o/day/yr sample was	
Submitted water well districted? Yes X No											
The state of the s									lued Clamped /elded		
2 PV		4 ABS		7 Fiber			Ouler (Specify	BCIOW)			
	asing Diam		to 17					ft., Dia	in.		
	_	-		ft.,	Dia Wolght	in R 68	L to lbs./ft.	,		to ft. .280	
Casing height above land surface 24 in., weight 3.68 lbs./ft. Wall thickness or gauge No280 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement											
1 Ste	el	3 Stainless Steel		5 Fiber	glass		8 RMP (SR)	11	other (specify)	
2 Bra	ISS	4 Galvanized steel		6 Concr	ete tile		9 ABS	12 1	None used (op	en hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes											
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATION INTERVALS: from 17 ft. to 34 ft., From ft. to ft.											
			from		f	t. to	ft., Fro		ft. to	ft.	
GRAVEL PACK INTERVALS: from 1!			15			ft., From		ft. to	ft.		
Ь—			from		f	t. to	ft., Fr		ft. to	ft.	
	OUT MAT		ent :	2 Cement gr	out	3 Be	entonite	4 Other ber	ntonite	hole plug	
1	ntervals:	-	· to 13	ft.	From	ft.	to	ft. From	13	ft. to 15 ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines			7	Dié malan			10 Livestock pens		14 Abandon water weli		
				7 Pit privy			11 Fuel storage 12 Fertilizer storage		15 Oil well/Gas well		
C CESS POOI							to differ (openly below)				
o Seepage pit									nery		
FROM			HOLOGIC LO	G		FROM	TO	How many fee	GING INTER	RVALS	
0	16	clay									
16	25	fine to me									
25	34	medium to	coarse	sand							
	ļ										
<u> </u>											
									W. 144		
							+				
						+					
								W-1		Alexander	
							-				
\vdash											
7 (20)	ump . co	Dic		rhi.		44)	(a.d. (C)			w implediction and	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)											
Well Contractor's License No236											
	Under the business name of HarpWell&PumpServiceInc by (signature)										
Jane Frederick											

_