1 LOC	ATION OF WA	ATER WELL:	FRACTION	Water Well Reco	ord Form WWC-	KSA 82a-1212 Section Number	Township Number	Range Number	
Ĥ	Sedgy	ai ck	NW 1/4	SW 1/4	SE 1/4	4	1 4-	157	
Distanc					SE III	*	T 27 s	R IE E/W	
Distance and direction frem nearest town or city street address of well if located within city? 1100 East 21st Street Wichita, Kansas									
	ATER WELL				<u>ita, Ka</u>	nsas			
		001101	AL REFINE				December of Academiteurs T	Divivsion of Water Resource	
	, ST. ADRESS, Y, STATE, ZIF		East 21st			65014	,		
		OCATION WITH 4	ta, Kansa	MPLETED WELL	67214 Application Number: TED WELL 36 ft. ELEVATION:			er:	
- 1	" IN SECTIO	N BOV.	Depth(s) groundw		1	ft. ELE	VATION: 2 ft.	3 ft.	
Ιt			, .	ATER LEVEL 1	=		FACE MEASURED ON mo/day/yr	04/26/1995	
		1 !	Pump tes		water was		ifter hours pun	,,	
] `	NW	Est	. Yield	*****	water was		after hours pun		
l ij v	,		re Hole Diameter	12 in.	to 36	ft.	and in.	to ft.	
\ \frac{1}{2} \ \frac{1}{2}	*	1 1 1 1 1 1	ELL WATER TO		5 Public wate			Injection well	
Ι.	<u></u>		1 Domestic	3 Feedlot	6 Oil field wa		9	Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
 		w	as a chemical/bacte	eriological sample s	submitted to D	epartment? Yes	No X; If yes, n	no/day/yr sample was	
S submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								•	
2 PV	C	4 ABS		7 Fiberglass			7	Threaded X	
Blank casing Diameter 6 in. to 16 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight 3.68 lbs./ft. Wall thickness or gauge No280									
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 16 ft. to 36 ft., From ft. to ft.									
ĺ			from	í	ft. to	ft., From	ft. to	ft.	
	GRAV	EL PACK INTERVAI	.S: from 14	<u>k</u>	ft. to 36 ft., Fr			ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Rentonite 4 Other hontonite hold plug								ft.	
Jestier Bentonite noie plug									
Grout Intervals: From 4 ft. to 12 ft. From ft. to ft. From 12 ft. to 14 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water we									
1 Septic tank 4 Lateral lines					11 Fuel sto				
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertiliz	13	15 Oil well/Gas well 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery									
Direction from well? How many feet?									
FROM	TO		HOLOGIC LOG	***************************************	FROM	TO	PLUGGING INTE	RVALS	
0	14	clay							
14	25	fine to me							
25	36	medium to	coarse s	and			14.	and the state of t	
								Plant of the second	
├—	1					- 			
<u> </u>									
		71.0							
							And the same of th		
		\-\\							
-									
CO	NTRACTO	R'S OR LANDOWNER'S C	ERTIFICATION: Thi	is water well was	(1) construct	ed, (2) reconstru	cted, or (3) plugged under n	ny jurisdiction and	
was completed on (mo/day/year)									
Under the business name of Harp Well & Pump Service. Inc. by (signature)									
Jane Frederick									
Onde	r the busin	ess name ofHax	p Well &	Pump Serv	ice, I	ໄຕ by (signa	ture)		