LOCATI	ION OF WATER		FRACTION	Water Well R	Record Form WWC-			
Ľ						Section Number	Township Number	Range Number
	Sedgwig			<u>14 SW 1/4</u>	SE 1/4	4	T 27 s	
Distance and direction frem nearest town or city street address of well if located within city?								
1100 East 21st Street Wichita, Kansas								
2 WATER WELL OWNER: COASTAL REFINERY								
RR#, ST. ADRESS, BOX #: 1100 East 21st Street Board of Agriculture, Divivsion of Water Resource								
CITY, STATE, ZIP CODE : Wichita, Kansas 67214 Application Number:								
J LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 37 ft. ELEVATION:								
	N SECTION BO	X:	Depth(s) grou	ndwater Encountere	ed 1	ft.	2 ft.	3 ft.
			WELL'S STATI	C WATER LEVEL	12.5 FI	. BELOW LAND SU	RFACE MEASURED ON mo/day/yr	04/26/1995
Pump test data: Well water was ft. after hours pumping gpm								
Est. Yield onm: Well water was ft after hours numning onm								
w <u>I</u>		F	Bore Hole Diame	ter 12 in.	. to 37	ft.	and in.	to ft.
= "		15	WELL WATER 1	TO BE USED AS:	5 Public wate	er supply	8 Air conditioning 11 I	njection well
.		, _	1 Domestic	3 Feedlot	6 Oil field wa		•	Other (Specify below)
	SW X	Sec	2 Irrigation	4 Industrial	7 Lawn and	garden only 1	0 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was								
S submitted Water Well Disinfected? Yes X No								
S TVDE OF CASING USED.								
S THE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								
2 PVC		4 ABS		7 Fiberglass		Saler (Speeny D	,	
Blank casing Diameter 6 in. to 17 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 24 in., weight 3,68 lbs./ft. Wall thickness or gauge No. ,280								
Casing height above land surface24in. ,weight3.68lbs. / ft.Wall thickness or gauge No280TYPE OF SCREEN OR PERFORATION MATERIAL:7 PVC10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass		Galvanized stee	a	6 Concrete tile		9 ABS	12 None used (op	
		RATION OPE			·		8 Saw cut	11 None (open hole)
1 Contino		3 Mill sk			Gauzed wrapped Vire wrapped		9 Drilled holes	II None (open note)
2 Louvere		4 Key pu			••			
					orch cut		10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 17 ft. to 37 ft., From ft. to ft.								
					ft. to	ft., From		ft.
					ft. to 37	ft., Fron		ft.
CICROU	T MATERI	AL: 1 Neat c	from	2 Cement grout	ftto	ft., Fron ntonite		<u>ft.</u>
-								hole plug
Grout Intervals: From 4 ft. to 12 ft. From						to 10 Livesto	ft. From 12	ft. to 14 ft.
What is the nearest source of possible contamination: 10 Livestock pens 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage								bandon water well
				-	•		150	Oil well/Gas well
0 0000 poor					0	13 Incential de storage		Other (specify below)
s water ugit sewer mits 6 Seepage pit 9 recuyaru relinery								
Direction from well? How many feet?								
FROM 1	TO		LITHOLOGIC LO	<u>JG</u>	FROM	то	PLUGGING INTE	RVALS
		lay						
			medium sa					
25 3		ealum t	o coarse	sand				
							- A.M	
		~~.				+		
							ap. 100 - 1	
لل حجم ا								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Con	ntractor's Li	cense No	236	This Water We	II Record was c	ompleted on (m	o/day/yr)Q5./.1	0/95
Under th	ne business	name ofHa	rp Well	& Pump Sei	rvice, I	Q.C by (sign	ature)	
Jane Frederick								