1 LOCA	TION OF WA	TER WELL:	FRACTION	Water Well Record	d Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick s			SW 1/4	NW 1/4 S	SE 1/4	4	T 27 s	150	
Distance and direction from nearest town or city street address of well if located within city?									
1100 East 21st Street Wichita, Kansas									
	TER WELL (L REFINE		a, Kan	343			
RR#,	ST. ADRESS,		ast 21st				Board of Agriculture,	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kans						67214	Application Number:		
		OCATION WITH 4		MPLETED WELL	38	ft. ELE	VATION:		
AN "X	" IN SECTIO	N BOX:	Depth(s) ground	vater Encountered	1	ft.	2 ft.	3 ft.	
1 1		WE	LL'S STATIC V	VATER LEVEL 1	2.98 FT.	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	04/27/1995	
	NW	NE	Pump tes	st data: Well	water was	ft. a	ifter hours pur	nping gpm	
<u> </u>			Yield	-	water was	ft. a	after hours pur		
∰ w	 		Hole Diameter	12 in.	to 38	ft.	and in.	to ft.	
		$\mathcal{N} + \mathbf{I} \mathbf{I}$	LL WATER TO	BE USED AS: 3 Feedlot	5 Public water 6 Oil field wa		-	Injection well Other (Specify below)	
i 1	sw		1 Domestic 2 Irrigation	4 Industrial	7 Lawn and g		0 Monitoring well	other (speerly below)	
ΙI	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was								
S submitted Water Well Disinfected? Yes X No									
TYPE OF CACING LICED.									
5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PVC 4 ABS 7 Fiberglass Threaded X									
Blank casing Diameter 6 in. to 18 ft., Dia in. to ft., Dia in. to ft.									
Casing helght above land surface 24 in., weight 3.68 lbs./ft. Wall thickness or gauge No280									
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Stee		3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specif	y)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 18 ft. to 38 ft., From ft. to ft.									
l	S		from		ft. to ft., Fro		ft. to	ft.	
	GRAV	EL PACK INTERVALS			ft. to 38 ft., Fro				
from ft. to ft., From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From 14 ft. to 16 ft.									
In From 19							Abandon water well		
1 Septic tank 4 Lateral lines			es	7 Pit privy		11 Fuel sto	rage 15	Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertilize	5	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery									
Direction from well? How many feet?									
FROM O	то 16		IOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS	
16	25	clay				 			
25	38	fine to me medium to							
	30	mearum co	COALSE S	anu	-		The state of		
								PWYW No. 1	
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						7.0		
						—			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Under the business name of Harp Well & Pump ServiceInc by (signature)									
							lane 3	Frederick	
							Ø 33.13		