1 LOCATION OF WATER WELL:		TER WELL:	FRACTION	Water Well Recon	d Form WWC-5	Section Number	Township Number	Range Number	
Sedgwick SW		SW 1/4	NW 1/4	SE 1/4	4	7 27 s	R 1E EW		
Distance and direction frem nearest town or city street address of well if located within city?									
1100 East 21st Street Wichita, Kansas									
ш	TER WELL		L REFINE				Doord of Academitors D	divivsion of Water Resource	
RR#, ST. ADRESS, BOX#: 1100 East 21st Street CITY, STATE, ZIP CODE: Wichita, Kansas 67214 Application Number									
				APLETED WELL	37		EVATION:	4:	
MAN "X	" IN SECTIO	N BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
l †		WE	LL'S STATIC W		3.38 FT	. BELOW LAND SUF	RFACE MEASURED ON mo/day/yr	04/27/1995	
	NW	NE	Pump tes		water was		after hours pum		
a			Yield e Hole Diameter	91	water was		after hours pum		
1Mile		I.	LL WATER TO 1	12 in. BE USED AS:	to 37 5 Public wate	ft. er supply	and in. 8 Air conditioning 11 I	to ft. njection well	
١.		K/ !	1 Domestic	3 Feedlot	6 Oil field wa		•	Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was								
submitted Water Well Disinfected? Yes X No TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PVC 4 ABS 7 Fiberglass Threaded X									
Blank casing Diameter 6 in. to 17 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight 3.68 lbs./ft. Wall thickness or gauge No280 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-cement 1 Steel 1 Steel 1 Steel 1 Steel 1 Steel 1 Steel 5 Fiberglass 1 Steel 1 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
	ered shutte			7 Torc	h cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 17 ft. to 37 ft., From ft. to ft.									
from GRAVEL PACK INTERVALS: from 15					. to . to 37	ft., From ft., From		ft.	
from					ft. to ft., Fr			fi. ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								hole plug	
Grout Intervals: From 4 ft. to 13 ft. From ft. to ft. From 13 ft. to 15 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water w									
1 Septic tank 4 Lateral lines					11 Fuel sto				
2 Sewer lines 5 Cess pool				8 Sewage lagoon			134	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery								nery	
Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							DVALC		
0	17	clay	iologic log	····	FROM	TO	PLUGGING INTE	RVALS	
17	25	fine to me	dium san	đ					
25	37	medium to							
							The state of the s		
		1/1							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Well Contractor's License No									
Jane Frederick									