LOCATIONO	WATER WELL:	EDACTION	Water Well Reco	ord Form WWC-		· · · · · · · · · · · · · · · · · · ·		
		FRACTION			Section Number	Township Number	Range Number	
	gwick	SW 1/4	<b>NW</b> 1/4	<b>SE</b> 1/4	4	<u>т 27 s</u>		
Distance and direction frem nearest town or city street address of well if located within city?								
1100 East 21st Wichita, Kansas								
2 WATER WEI	LL OWNER: COAST	AL REFINE	RY					
RR#, ST. ADRESS, BOX #: 1100 East 21st Street Board of Agriculture, Divission of Water Resource								
CITY, STATE, ZIP CODE : Wichita, Kansas 67214 Application Number:							r:	
<sup>3</sup> LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL <b>30</b> ft. ELEVATION:								
AN "X" IN SEC	TION BOX:	Depth(s) groundwa	ater Encountered	1	ft.	2 ft.	3 ft.	
		ELL'S STATIC W		L5 FT	. BELOW LAND SUR	FACE MEASURED ON mo/day/yr	05/15/1995	
		Pump test		water was	ft. a	fter hours pum		
	WNE	t. Yield		l water was		ifter hours pum		
w With	T Bo	re Hole Diameter	8 in.	to 30	ft.	and in.	to ft.	
ĭ₹w	L	ELL WATER TO H		5 Public wate			njection well	
	X.,	1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)	
5	wSHE	2 Irrigation	4 Industrial	7 Lawn and g		) Monltoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was								
A TYDE OF CASING LIGED.								
5 wrought from a Concrete the CASHOROMAN. Gried Champed								
2 PVC 4 ABS 7 Fiberglass Threaded								
Blank casing Diameter 2 in. to 9 ft., Dia in. to ft., Dia 2 in. to 29-30 ft.								
Casing height above land surface 24 in., weight . 703 lbs. / ft. Wall thickness or gauge No154								
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement   1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass4 Galvanized steel6 Concrete tile9 ABS12 None used (open hole)								
	PERFORATION OPENI	NG ARE:	5 Ga	uzed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 9 ft. to 29 ft., From ft. to ft.								
		from	1	ft. to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 7.			5	ft. to 29 ft., From		ft. to	ft.	
		from	1	ft. to	ft., From	ft. to	ft	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals: From 0 ft. to 3 ft. From 3 ft. to 7, 5 ft. From ft. to ft.								
What is the nearest source of possible contamination:			-	10 Livestock pens		•	bandon water well	
1 Septic tank 4 Lateral lines			7 Pit privy 11 Fue		11 Fuel stor	rage 15 (	Dil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lag	8 Sewage lagoon 12 Fertilize			Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery								
Direction from well? How many feet?								
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0 15	dark gray	clay						
15 17	fine sand	_						
17 30	medium coa	arse sand						
		· · · · · · · · · · · · · · · · · · ·						
<b>├</b>								
	······							
┟┯┯┷┷								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No								
Under the business name of Harp Well & Pump Service, Inc. by (signature)								
fane Frederick								