1 LOCATION OF WATER WELL:			FRACTION	Wate	r Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick		SE	/4 NW	1/4 SI	E 1/4	4	T 27 s	R 1E EW		
Distance and direction frem nearest town or city street address of well if located within city?										
1100 East 21st Street Wichita, Kansas										
	TER WELL		TAL REFI							
RR#,	ST. ADRESS	BOX#: 1100	East 21	st Stre	et			Board of Agriculture,	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kansas					67214			Application Number:		
		LOCATION WITH 4	DEPTH OF	COMPLETED	WELL	33	ft. ELI	EVATION:		
A	" IN SECTIO	N .	- 170	ndwater Enco		1	ft.	2 ft.	3 ft.	
			WELL'S STATI					RFACE MEASURED ON mo/day/yr	04/24/1995	
'	NW	NE	-	test data:		ater was		after hours pur		
<u> </u>	•		st. Yield	gpm:		ater was	ft.	after hours pur		
lig w	-	I I	ore Hole Diame			o 33	ft.	and in.	to ft.	
			VELL WATER ' 1 Domestic	TO BE USED. 3 Feedle		Public water Oil field wa		_	Injection well Other (Specify below)	
	sw		2 Irrigation	4 Indust		Lawn and g		10 Monitoring well	culti (aproli) zelotty	
		_v	-	acteriological		_	•	•	mo/day/yr sample was	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No										
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped										
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									•	
2 PVC		4 ABS		7 Fiber	glass				Threaded X	
Blank casing Diameter 6 in. to 18 ft., Dia in. to ft., Dia in. to ft.										
Casing height above land surface 24 in., weight 3.68 lbs./ft. Wall thickness or gauge No280										
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)										
1 Ste		3 Stainless Steel		ū				11 other (specif		
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR REPEOPLATION OPENING ARE. 8 Saw cut 11 None (open hole)										
SCALLEN ON TENTON OF ENTING ARE: Scalled wrapped										
21 manual design of the second										
SCHEEN BEDEON ATION INTERPOLATION										
SCREE	N-FERFO	RATION INTERVA		18		∞ 33	ft., From		ft.	
	CDAM	EL PACK INTERVA	from ALS: from	ft. to 16 ft. to 33			ft., Fron ft., Fron		ft.	
	GRAV	EL FACK INTERVA	from	10	n. to 33		ft., Fron			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From 14 ft. to 16 ft.										
What is the nearest source of possible cont			contamination:				10 Livesto	,	Abandon water well	
1 Septic tank 4 Lateral			lines	es 7 Pit privy			11 Fuel st	orage 15	Oil well/Gas well	
2 Sewer lines 5 Cess po			ool	8 Sewage lagoon		n		-1.34	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery									inery	
Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							10x/4x G			
O	то 16	clay	I HOLOGIC L	OG		FROM	то	PLUGGING INTE	KVALS	
16	24	medium sa	ากส้							
24	33	medium to		sand						
			77.10.4							
 	ļ									
	ļ						-			
	 				-					
				***************************************			-			
				7.4			+ +			
								1 41 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
			1000							
7 CON	L					1	<u> </u>			
Contractor box ballowner acertification: Tills water well was (1) constructed; (2) reconstructed; or (4) plugged under my jurisdiction and										
was completed on (mo/day/year)										
Under the business name of Harp Well & Pump Service. Inc by (signature)										
Jane Frederick										
								<i>#</i> ~.~~ 0		