1 LOC	ATION OF W	ATER WELL:	FRACTION	Water Well Recor	d Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number
	Sedgr	vi ck	SW 1/4	NE 1/4	SE 1/4	4	T 27 s	R 1E EW
Distanc		frem nearest town or city stree				-	1 27 3	1 R DW
1100 East 21st Street Wichita, Kansas								
	ATER WELL		L REFINE		LOG/ NG			
RR#	, ST. ADRESS		ast 21st				Board of Agriculture,	Divivsion of Water Resource
CIT	Y. STATE, ZI		a, Kansa			67214	Application Num	ber:
			DEPTH OF COM	MPLETED WELL	36	ft. ELE	VATION:	
AN "	K" IN SECTIO	N BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.
		WE	LL'S STATIC W			BELOW LAND SUR	RFACE MEASURED ON mo/day/yr	04/24/1995
	NW	NE	Pump tes		water was		after hours pu	
ile		1 !	Yield	O1	water was		after hours pu	
1Mile	v	L	e Hole Diameter LL WATER TO	12 in. REJISEDAS:	to 36 5 Public water	ft. rennnly s	and in. 8 Air conditioning 11	to ft. Injection well
Ι.		!V	1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)
	SW		2 Irrigation	4 Industrial	7 Lawn and g	arden only 1	0 Monitoring well	
		Was	a chemical/bacte	eriological sample s	ubmitted to De	partment? Yes	No X; If yes,	mo/day/yr sample was
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								
2 PV		4 ABS	4. 10	7 Fiberglass				Threaded X
	asing Dian	neter 6 in. ve land surface 24	to 19	ft., Dia welght 3	in.) 60	to lhs./ft. \	ft. , Dia in. Wall thickness or gauge No.	to ft. .280
		EN OR PERFORATION	in., N MATERIAL:	weight 3		PVC	10 Asbestos-cei	
1 St	ee!	3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (speci	fy)
2 Bra	ISS	4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (pen hole)
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Cont	ino us slot	3 Mill slot		6 Wire	e wrapped		9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 19 ft. to 36 ft., From ft. to ft.								
!			from		. to	ft., From		ft.
GRAVEL PACK INTERVALS: from 16				,		ft., From	•	
from ft. to ft., From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From 14 ft. to 16 ft.								
What is the nearest source of possible contamination:					10 Livestoc	,	Abandon water well	
1 Septic tank 4 Lateral lines		es	7 Pit privy		11 Fuel sto	orage 15	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon			dda atamana	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage refinery								
Directi FROM	on from we		HOLOGIC LOG		FROM	то	How many feet? PLUGGING INT	EDVALS
0	18	clay	IOLOGIC LOG		FROM	1 10	FLUGGING INT	ERVALS
18	25	fine sand						
25	30	clay						
30	36	medium san	d					
	ļ					-		
	-							
	-							
		17 Avrilla II.				-		
	1						10. 4 (A)	THE RESERVE OF THE PARTY OF THE
	-							
	<u> </u>							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No								
unae	r ine busii	iess name ofAA.D.	R	v::wii.P:::::3:2:4:'A'	<i>₩</i> .₩.¥₩.¥	Na Dy (signa	()ana	Frederick
							June c	vecue ucro