


LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Neosho</u>	$\frac{1}{4}$ $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	<u>27</u>	T <u>27</u> S	R <u>18</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

See Attached Sketch

WATER WELL OWNER: <u>City of Chanute</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>P.O. Box 907</u>	Application Number:
City, State, ZIP Code: <u>Chanute, Kansas 66720</u>	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: <u>23.0</u> ft. ELEVATION: <u>Contact P.D.: 915.55</u>
	Depth(s) Groundwater Encountered 1. <u>19.0</u> ft. 2. <u>23.0</u> ft. 3. <u>23.0</u> ft. WELL'S STATIC WATER LEVEL <u>10.30</u> ft. below land surface measured on mo/day/yr <u>04/30/01</u> Pump test data: Well water was <u>23.0</u> ft. after <u>04/30/01</u> hours pumping <u>04/30/01</u> gpm Est. Yield <u>23.0</u> gpm: Well water was <u>23.0</u> ft. after <u>04/30/01</u> hours pumping <u>04/30/01</u> gpm Bore Hole Diameter <u>8.25</u> in. to <u>23.0</u> ft., and <u>23.0</u> in. to <u>23.0</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> <u>MW-14</u> Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> No. <u>No</u> ; If yes, mo/day/yr sample was submitted <u>No</u> Water Well Disinfected? Yes <u>No</u> No. <u>No</u>

TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>Clamped</u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	<u>Threaded</u>
Blank casing diameter <u>2.0</u> in. to <u>13.0</u> ft., Dia. <u>13.0</u> in. to <u>13.0</u> ft., Dia. <u>13.0</u> in. to <u>13.0</u> ft.			
Casing height above land surface <u>13.0</u> in., weight <u>13.0</u> lbs./ft. Wall thickness or gauge No. <u>13.0</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<u>1 Mill slot</u>	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>13.0</u> ft. to <u>23.0</u> ft., From <u>13.0</u> ft. to <u>23.0</u> ft.		
GRAVEL PACK INTERVALS:	From <u>10.5</u> ft. to <u>23.0</u> ft., From <u>10.5</u> ft. to <u>23.0</u> ft.		

GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	4 Other
Grout Intervals:	From <u>2.0</u> ft. to <u>10.5</u> ft., From <u>2.0</u> ft. to <u>10.5</u> ft.			
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				<u>16 Other (specify below)</u>
				<u>Landfill</u>

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0' 2.5' Topsoil	
2.5' 5' Silty clay, brown with gray + red brown mottling	
5' 10' Silty clay, gray with brown + red brown mottling	
10' 15' Clay, brown with gray + red brown mottling	
15' 18.5' Sandy clay, brown, gray, dark brown + red brown mottled	
18.5' 22.5' Clayey sand, brown with gravel	
22.5' 23' Limestone, weathered	
23' Auger Refusal	

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/27/01</u> and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. <u>416</u> This Water Well Record was completed on (mo/day/yr) <u>04/26/01</u>
under the business name of <u>416 Terracon</u> by (signature) <u>[Signature]</u>