


LOCATION OF WATER WELL: Fraction  $\frac{1}{4}$   $\frac{1}{4}$  SW  $\frac{1}{4}$  Section Number 27 Township Number T 27 S Range Number R 10 EW  
 County: Neosho

Distance and direction from nearest town or city street address of well if located within city?  
 See Attached Sketch

WATER WELL OWNER: City of Chanute  
 RR#, St. Address, Box #: P.O. Box 907 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Chanute, Kansas 66720 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: DEPTH OF COMPLETED WELL: 18.5 ft. ELEVATION: Concrete Pad: 912.55  
 AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1. 16.0 ft. 2. ft. 3. ft.



WELL'S STATIC WATER LEVEL: 15.60 ft. below land surface measured on mo/day/yr 04/30/01  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm: Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 8.25 in. to 10.5 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well m.w. - 15  
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Threaded  
 Blank casing diameter 2.0 in. to 8.5 ft., Dia in. to ft., Dia in. to ft.  
 Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 2 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 3 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 8.5 ft. to 18.5 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 6.5 ft. to 18.5 ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout intervals: From 2.0 ft. to 6.5 ft., From ft. to ft., From ft. to ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Land fill  
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	3'	Topsoil			
3'	5'	Clayey silt, brown			
5'	6'	Silty clay, brown			
6'	10'	Clay, trace silt & sand, brown with red brown & gray mottling			
10'	16.5'	Clay, trace silt, brown with gray & red brown mottling			
16.5'	18'	Sandy clay with gravel, brown			
18'	18.5'	Limestone			
18.5'		Augia Refusal			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/20/01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 06/26/01 under the business name of Terracon by (signature)