2	2-5	W	ATER WELL REC	ORD Form	WWC-5	KSA 82a-	-1212 ID I	No.			
1 LOCAT	TION OF WA	ATER WELL:	Fraction	OND TOIM	/////////		ction Number		umber	Range Numb	er
County:	Neas	ho	NE 14	SW 1/4	NE 14		28	T 27	s	R 18 (	Dw.
Distance a	nd direction	from nearest to	wn or city street a	address of well	if located wi	ithin city?	. ,		,		
Nex.	<del></del>	the City	ot Chans	te Piblic	Work	facil	ity leg	14 Mst- a	w S. K	aty Ave.	
	R WELL OW		co Phillips Phillips b	Wildings			•				
RR#, St. AcCity, State,	ddress, Box							Board of Ag Application		ivision of Water Res	ources
			esville, 6K 4 DEPTH OF C		/EII "	20	# FLEV	ATION:			
	: WELL'S LO N SECTION		_					ft. 2			
, ,	N N							ice measured on mo			
		;	Pur	mp test data:	Well water v	was <del></del>	ft.	after	hours po	ımping	gpn
NW NE Est. Yield g					. gpm: Well water wasft. afterhours pumping EUSED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
		`	1 Domestic		6 Oi	l field wate	r supply	9 Dewatering	12 O	ther (Specify below)	
w	i	<del></del>	2 Irrigation	4 Industri	al 7 Do	omestic (la	wn & garden)	Monitoring well			
	-	-						سلا	_		
-	-sw -	SE	l/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs sample was s Water Well Disinfected? Yes								
	<u> </u>	·	mitted				v	vater vveii Disinfecte	u? res	No _	-
5 TVDE (	S	0400000000									
5 TYPE (		CASING USED: 3 RMP (S	5 Wrought iron 6 Asbestos-Cement		8 Concrete tile 9 Other (specify below)			CASING JOINTS: Glued C Welded			
EPVC 4 ABS				7 Fiberglass					Threa	Threaded	
Blank casir	ng diameter	·	in. to	5	ft., Dia		in. to	ft., Dia		in. to	ft
				in., weight				lbs./ft. Wall thickne	ss or guag	e No. Sc4. 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:						PVC 10 Asbestos-Cement 8 RMP (SR) 11 Other (Specify)					
1 Steel 3 Stainless Steel 5 Fibe 2 Brass 4 Galvanized Steel 6 Cor						9 AE			er (Specily) e used (op		
		RATION OPENII	NGS ARF			dwrapped		8 Saw cut		11 None (open ho	le)
						wrapped 9 Drilled hole					•
2 Louv	vered shutte		(ey punched	_	7 Torch c				-		
SCREEN-F	PERFORAT	ED INTERVALS			.ft. to	20	ft., Fror	n	ft. to		ft
(	GRAVEL PA	CK INTERVALS	From	3	. ft. to		ft., Fror	n n	ft. to		tt
`	CITAVELTA	OK IIVI ETTVALO	From	·	. ft. to		ft., Fror	n	ft. to		ft
0.000	IT MATERIA					_					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout  Grout Intervals: From						Ben	tonite	4 Other			
			contamination:		11	П.				π. τοbandoned water we	
	otic tank		7 Pit privy			storage	15 Oil well/Gas well				
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool				8 Sewage lagoon			12 Fertilizer storage		(16) Other (specify below)		
3 Wat	tertight sewe		9 Feedyard			cticide storage		Refinery	<b>T</b>		
Direction fr	om well?	_					How ma	any feet? —			
FROM TO LITHOLOGIC LOG						FROM TO			PLUGGING INTERVALS		
0	20	Silly Cl	ay								
		•					<b></b>		· · · · · · · · · · · · · · · · · · ·		
	-								_/	<u> </u>	
								$\overline{}$			-
							-	$\overline{}$			
								/			
							6				
										: :	
7											
		OR LANDOWNE						constructed, or (3) p			
			710	т.	nis Water W	ell Record	and this r	ecord is true to the beed on (mo/day/yr)	est of my kn	owledge and belief.	∧a⊓sas
	usiness nan		6 our Sota		Trater VV	511 1 10001U		(signature)	1/2	$\sim$	
				<i></i>						-	

INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well.