
LOCATION OF WATER V		Fraction				ion Number	Townsi	nip Number	Rang	e Number	
county: Neosl			sw 1/4			16	T	27 s	R	18	E
Distance and direction from n	earest town o										
20 N. Santa Fe, Chanu											_
WATER WELL OWNER:					_	_					
RR#, St. Address, Box # :									vision of Wa	ter Resourc	ces
City, State, ZIP Code :	Topeka,	KS_6661	2	Chanu	te, c	S late 72	Applicati	on Number:			
LOCATE WELL'S LOCAT AN "X" IN SECTION BOX	ON WITH 4	DEDTH OF	COMPLETED	/F1.1	12	A [15)	/ATION:	029	ON (TO	-1	
AN X IN SECTION BOX		TOEL IH OF	COMPLETED	/ELL	!3	H. ELEY	ATION:	920	2.00 (100	٠٤	
	1 10	eptn(s) Grou	indwater Encounte TIC WATER LEVE	ered 1	7	π	. 2	π.	· 3	2142106	ft.
NW NI	E W										
		Pu	mp test data: V	ell water was	•	f	t. after	hours	pumping _	gr	om
W W	E E	st. Yield	gpm: W	ell water was	•	f	t. after	hours	pumping _	gr	om
	_ B	ore Hole Dia	meter 8.25	in. to	15) 	ft. and		in. to		ft.
SW SI	E1 W	LLL WATER	R TO BE USED As stic 3 Feed lot	5: 5 Public 6 Oil fie	: water su Id water s	ippiy supply	9 Dewa	naitioning terina	11 Injection 12 Other (S	well necify belo	w)
x									12 04101 (0	poony boile	"'
S			on 4 Industrial								
	l l		al/bacteriological	sample subm	nitted to E						15
		ubmitted						nfected? Yes		No X	
TYPE OF BLANK CASING			5 Wrought					JOINTS: Glu		Clamped _.	
1 Steel	•	₹)	6 Asbestos	-Cement 9	Other	(specify belo	w)	We			
2 PVC	4 ABS		7 Fiberglas	is				Thre	aded	Flush	
Blank casing diameter	2 in	n. to	3 ft., Dia		in. t	0	ft., Dia		in. to		_ft.
Casing height above land sur	face Flu	shmount	in., weight	0.7	03	lbs./ft.	Wall thickne	ss or gauge No	o. S	CH. 40	
YPE OF SCREEN OR PER					7	PVC	10	Asbestos-cen	nent		
1 Steel	3 Stainless	steel	5 Fiberglas	S	8						
	4 Galvaniz		5 Fiberglas 6 Concrete	tile	9	ABS	12	Other (specify None used (o	pen hole)		
SCREEN OR PERFORATION				Gauzed w	rapped		8 Saw cu	ıt	11 None	(open hole	;)
 Continuous slot 	3 Mi	ill slot	6	Wire wrap	ped						
2 Louvered shutter	4 Ke	• •		7 Torch cut			10 Other	(specify)			
CREEN-PERFORATED INT	TERVALS:	From	3 ft.	to	13	ft. F	rom	ft	. to		_ft.
		From	ft.	to		ft. F	rom	ft	. to		ft.
GRAVEL PACK INTE	ERVALS:	From	2.5 ft.	to	13	ft. F	rom	ft	. to		_ft.
				to					. to		ft.
GROUT MATERIAL:	1 Neat cer		2 Cement grout		3 Ben	tonite	4 Other				
Grout Intervals From											
What is the nearest source of					' '		tock pens		bandoned v		-
1 Septic tank	•		es 7	Pit privv		11 Fuel	storage		Oil well/ Gas		
2 Sewer lines	5	Cess pool	8	Sewage lag			izer storage		Other (specif		
3 Watertight sewer line		Seepage (Feedyard			cticide storag		,-,	. ,	
Direction from well?		,		,		How many	-				
FROM TO C	ODE		IOLOGIC LOG		FROM	ТО		PLUGGING	INTERVAL	S	
0 7		- yellow									
7 15			yellow brown	10.5							
			from 15 to	13 feet.							
	weii	set at 13	s reet.								
				——————————————————————————————————————							
7 CONTRACTOR'S OR LA	NDOWNER'S	S CERTIFIC	ATION: This water	er well was (1) constru	cted, (2) rec	onstructed, o	r (3) plugged u	nder my juris	diction and	was
completed on (mo/day/yr)								est of my know			
Water Well Contractor's Lice								ompleted on (r			
under the business name of			nical Service	s Inc.		y (signature)		water of his			
INSTRUCTIONS:. Please										ater, 1000 S	w
Jackson St., Ste. 420, Top										,	