


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Neosho	SW 1/4 SE 1/4 NE 1/4	20	T 27 S	R 18 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 240 ESE of SE corner of 202 W Main-Chanute, Kansas

2 WATER WELL OWNER: Crescent Oil	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 202 W. Main Street	Application Number:
City, State, ZIP Code: Chanute, Kansas 6672-	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 13.5 ft. ELEVATION:
	Depth(s) Groundwater Encountered: 9.5 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL: 9.5 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter: 6 in. to 14.5 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: 2 in. to 3.5 ft., Dia. Sch 40			Threaded: X
Casing height above land surface: 0.0 in., weight Sch 40			lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 3.5 ft. to 9.0 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 3.0 ft. to 13.5 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0.0 ft. to 3.0 ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	

Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.5	Concrete			
0.5	2.0	Br Dr Br L C1			
2.0	3.5	Red Br weathered sandstone			
4.0	7.0	Pale Org Br Sandstone			
7.0	10.0	Gr Br Sandstone			
10.0	11.0	Org Br Sandstone			
11.0	14.5	Lt Br Gr Sandstone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/4/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 2/4/92 under the business name of Terracon Consultants SE, Inc. by (signature) [Signature]
