WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL: County: Neosho	Fraction - 1/4 SW 1/4 SE 1/4 NE 1/4	Section Number Township No. Range Number 28 T 27 S R 18 \(\overline{\mathbb{Z}} \) E \(\overline{\mathbb{W}} \)	
Street/Rural Address of Well Location;	if unknown distance & direction	Global Positioning System (GPS) information:	
from nearest town or intersection: If at	owner's address, check here \[\square.	Latitude: .N.37.66950	
Former Continental Refinery		Longitude: W.9543775 (in decimal degrees)	
E 14 St. & Katy Rd, Chanute, KS	MW-21	Elevation: unknown	
		<u>Datum</u> : ☑ WGS 84, □ NAD 83, □ NAD 27	
DD 11 C	Phillips Company RM and R	Collection Method:	
O'to Ototo ZID Oo to	uth Keeler Avenue	☐ GPS unit (Make/Model: Garmin Geko 101)	
City, State, ZIP Code : Bartlesv	ville, OK 74004	Digital Map/Photo, Topographic Map, Land Survey	
Est. Accuracy: ☐ <3 m, ☑ 3-5 m, ☐ 5-15 m, ☐ >15 m			
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 23 ft.			
		ft. (2) ft. (3) ft.	
N WELL'S STAT	N WELL'S STATIC WATER LEVELunkft. below land surface measured on mo/day/yr		
Pump test data: Well water wasft. after hours pumping gpm			
NW NE EST. YIELD. ≤50gpm. Well water wasft. after			
W E Bore Hole Diameter 8 in. to .23 ft., and			
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)			
Irrigation			
Was a chemical/bacteriological sample submitted to Department? Yes No			
S If yes, mo/day/yr sample was submitted			
1 mile Water well disinfected? ☐ Yes ☑ No			
5 TYPE OF CASING USED: Steel PVC Other			
CASING JOINTS: Glued Clamped Welded Threaded			
Casing diameter .2 in. to .23 ft., Diameter ft., Diameter ft.			
Casing height above land surface. 30 in., Weight 0.682 lbs./ft., Wall thickness or gauge No0.154"			
TYPE OF SCREEN OR PERFORATION	MATERIAL:		
☐ Steel ☐ Stainless Steel	Z PVC □	Other (Specify)	
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)			
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)			
SCREEN-PERFORATED INTERVALS: From			
From			
GRAVEL PACK INTERVALS: From			
6 CDOUT MATERIAL. Next come	ent Cement grout P Penton	ite Other	
Grout Intervals: From .0	11 ft From	t. to ft., From ft. toft.	
What is the nearest source of possible conta	omination:	t. to tt., 110iii tt. tott.	
	es Pit privy Livestock p	ens Insecticide storage Other (specify below)	
Sewer lines Cesspool Sewage lagoon Full Fuel storage Abandoned water well			
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well			
	Distance f	rom wellunknown	
FROM TO LITHOLOG	IC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0 15 It brown, fat clay			
15 23 gray, silty sandy clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged			
under my jurisdiction and was completed on (mo/day/year) .1.1/1.0/20.10 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No616 This Water Well Record was completed on (mo/day/year) 1/20/2011			
under the business name of . Thiele Geotech, Inc. by (signature)			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies			
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at			
http://www.kdheks.gov/waterwell/index.html.			
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy			