WATER WELL R		WWC-5		ision of Wate				
Original Record		ge in Well Use		ources App. N		Well ID		
1 LOCATION OF WATER WELL:		Fraction						
County: Neosho		1/4 SE 1/4 SW 1/4						
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and								
Business: Phillips 66 direction from nearest town or intersection): If at owner's address, check here:								
Address: 1708-02 Phillips Building Address: Former Cooperative Refinery								
City: Bartlesville State: OK ZIP: 74004 980 E 14th St, Chanute,KS								
3 LOCATE WELL					24			
WITH "Y" IN 4 DEPTH OF COMPLETED WELL:40 ft. 5 Latitude:								
SECTION BOX:	Depth(s) Groundwater Encountered: 1) It.				tude: -95.438	504(decimal degrees)		
N	2)					4 ■ NAD 83 □ NAD 27		
NIA OUR TO LO DUTTE OF THE PARTY OF THE PART								
,,,,, ,,,,,	NA					■ GPS (unit make/model:) (WAAS enabled? □ Yes □ No)		
NW NE	- NW NE -				☐ Land Survey ☐ Topographic Map			
W E					Online Mapper: Google Earth			
"	Well water wasNA ft.							
SW SE	anter							
	Estimated Yield: NAgpm			6 Elevation: 924				
_	Bore Hole Diameter: 3.25 in. to				Other			
1 mile NA in. toNA ft.								
		atam Cummlan, small ID		10 🗖 0:	Field Water Consules: to			
1. Domestic:		ater Supply: well ID				ease		
☐ Lawn & Garden	,							
Livestock				12. Geothermal: how many bores?				
2. Irrigation	9. Environmental Remediation: well ID AS-37				a) Closed Loop Horizontal Vertical			
3. ☐ Feedlot					b) Open Loop Surface Discharge Inj. of Water			
4. Industrial	☐ Recovery			13. 🔲 Ot	her (specify):			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:								
Water well disinfected? ☐ Yes ■ No								
8 TYPE OF CASING	USED: ☐ Steel ■ PV	/C \(\square\) Other	CASI	NG JOINTS	: Glued Clamped	I □ Welded ■ Threaded		
8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other								
Casing diameter 2 in to 26 ft., Diameter NA in to NA ft., Diameter NA in to NA ft. Casing height above land surface 12 in Weight NA lbs./ft. Wall thickness or gauge No. SCH 40								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot ■ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)								
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)								
SCREEN-PERFORATED INTERVALS: From .26 ft. to .28 ft., From .NA ft. to .NA ftNA ft. to .NA ftNA f								
GRAVEL PACK INTERVALS: From 25 ft to 28 ft, From NA ft to NA ft, From NA ft to NA ft.								
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other Granular bent- 24.5-25.0 Grout Intervals: From ☐ ft. to ☐ ft., From ☐ ft. to ☐ ft.								
Nearest source of possible contamination:								
Septic Tank								
■ Sewer Lines □ Cess Pool □ Sewage Lagoon □ Fuel Storage □ Abandoned Water Well								
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well								
☐ Other (Specify) Direction from well? West Distance from well? >100' ft.								
			ell? >100'					
10 FROM TO	LITHOLO	GIC LOG	FROM	TO	LITHO. LOG (cont.) or	PLUGGING INTERVALS		
Notes:								
Direct Push- no sampling conducted								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year) .1.1/7/16								
under the business name of Eagle Environmental Consulting, Inc. Signature								
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,								
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
I .	gov/waterwell/index.html		KSA 82a-12			Revised 7/10/2015		