


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>NW 1/4 NW 1/4 NW 1/4</u>	Section Number <u>18</u>	Township Number T <u>27</u> S	Range Number R <u>2</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>6327 E. 13th, Wichita, KS.</u>					
2 WATER WELL OWNER: <u>Amoco Oil Co.</u> RR#, St. Address, Box #: <u>8700 Indian Creek Pkwy; Suite 190</u> Board of Agriculture, Division of Water Resources City, State, ZIP Code: <u>Overland Park, KS. 66210</u> Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <u>19'</u> ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. <u>7-8'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>4.24</u> ft. below land surface measured on mo/day/yr <u>6-23-95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8 1/2"</u> in. to <u>19'</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2.375</u> in. to <u>4'</u> ft., Dia in. to ft., Dia in. to SDR <u>13</u> ft. Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH. 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>19'</u> ft. to <u>4'</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>19'</u> ft. to <u>3'6"</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3'6"</u> ft. to <u>2'6"</u> ft., From <u>2'6"</u> ft. to <u>0'</u> ft., From ft. to ft. What is the nearest source of possible contamination: <u>2</u> 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy <u>11</u> Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? <u>West</u> How many feet? <u>100'</u>					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	.50	Asphalt			
.50	4	Blk clay to silty clay, firm, organics, mod. odor.			
4	6	Blk clay w/ some fine grained sand, moist, mod. odor.			
6	11	Olive-yellowish gray shaley clay w/ caliche len at 7'. no odor, moist.			
11	12.50	Red brn clay grading to shaley clay. Dry, no odor.			
12.50	19'	Green gray clay, dry, no odor, friable, low plasticity.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-10-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>6-28-95</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>					