Loca	TION OF WA	TED MELL.	FRACTION	J	Water Well Re	cord Form WWC	Section Number	T		Range Number
ساس			NW NW	1/4 NE	1/4	SE 1/4	10	Township Number		215
Sedqwick NW 1/4 NE 1/4 SE 1/4 10 T 27 S R 2E Distance and direction from nearest town or city street address of well if located within city?									R ZE E/W	
12528 Castlewood Dr. Wichita, Kansas										
water well owner: KONOZIOLA, Joey										
	ST. ADRESS,	11010			Dr.				Agriculture, Divivsio	n of Water Resource
	, STATE, ZIP								ication Number:	
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.										
l +		_N 1	. ,,,				ft.	2 SURFACE MEASURED ON		3 ft. 9/14/1995
				IC WATER		30 ¹ Il water was			hours pumping	
'	NW	NE	Yleld	gpi		ell water was	ft. ft.		hours pumping	gpm gpm
¥gw		1 1 1	Hole Dian		.2 in.	to 80	ft.	and	in. to	
Į ≅w		N IE		R TO BE US		5 Public wa	=	8 Air conditioning	11 Inject	1
Ι.		975	1 Domestic	3 F	cedlot	6 Oil field v	vater supply	9 Dewatering		(Specify below)
	SW.		2 Irrigation	1 4 Ir	ıdustrial	7 Lawn and	garden only	10 Monitoring well		
↓	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was									
S submitted Water Well Disinfected? Yes X No 5 TYPE OF CASING USED: 5 Wrought from 8 Concrete tile CASING JOINTS: Clued X Clamped										
5 TY		_			Vrought iro sbestos-Ce		8 Concrete tile	CASING JOIN	Giaca	X Clamped
1		3 RMP (SR)			-		9 Other (Specify	below)	Welde Threa	
ZIVC 4ABS SDR-20										
Blank casing Diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214										
Casing height above land surface 12 in. , weight 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)										
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)										
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATION INTERVALS: from 40 ft. to 80 ft., From ft. to ft.										
from					ft. to		ft., Fro		ft. to	ft.
GRAVEL PACK INTERVALS: from 24					ft. to 80 ft. to		ft., Fr ft., Fr		ft. to ft. to	ft. fr
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.										
What is the nearest source of possible contamination:								tock pens	14 Aband	lon water well
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel	•	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool					8 Sewage la	J		Mzer storage	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent									pparent	
Direction FROM	n from we		HOLOGIC	LOC		FROM	1 TO	How many feet?	NG INTERVAL	I S
0	4	topsoil	IOLOGIC	LOG		FROM	1	12000	ING INTERVA	
4	35	clay								
35	70	shale						<u> </u>		
70	80	limestone								
l										
						 				
		, , , , , , , , , , , , , , , , , , , ,								
ļ			,			<u> </u>				
	L		2			<u> </u>				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and										
was completed on (mo/day/year)										
Under the business name of Harp Well & Pump Service. Inc by (signature)										
Juder	THE DUSIL	1005 HaiffC VI#\$#######	/A.W.M.M	TV	rgrmi.MA		uuruum ni lad	0,	ine Fred	derick
I								<i>₹</i> [∞]		