				Water Well Rec	ord Form WWC-		·····		
1 LOCATION OF WATER WELL:			FRACTION			Section Number	Township Number	Range Number	
			<u>NE</u> 1/4	NE 1/4	SE 1/4	10	T 27 s		
stance and direction frem nearest town or city street address of well if located within city?									
12619 E. Tallowood Dr. Wichita, Kansas									
5			T, Mark				Roard of Agriculture, D	ivivsion of Water Resource	
	ST. ADRESS		19 E. Tallo			67206	2 .		
	', STATE, ZI I		hita, Kansa			<u>67206</u>	Application Number	r:	
	TE WELL'S I " IN SECTIO	OCATION WITH N BOX:	4 DEPTH OF CON Depth(s) groundw		80 1	ft. ELEV ft.	VATION: 2 ft.	3 ft.	
l t	[- <u>N</u>	WELL'S STATIC W				Z IL. FACE MEASURED ON mo/day/yr	10/09/1995	
			Pump test		uo 🗠 🗠		fter hours pum		
	NW	NE	Est. Yleid		l water was		iter hours pum		
ž, v			Bore Hole Diameter	12 in.	to 80	ft.	and in.	to ft.	
<u> </u>			WELL WATER TO		5 Public wat			njection well	
			1 Domestic	3 Feedlot	6 Oil field w			Other (Specify below)	
	SW	SFE	2 Irrigation	4 Industrial	7 Lawn and) Monitoring well		
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was							10/day/yr sample was	
	S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PVC	2	4 ABS		7 Fiberglass	S	SDR-26	ן	hreaded	
Blank c	asing Dian	eter 5	in. to 30	ft., Dia	in	. to	ft., Dia in.	to ft.	
-	-	ve land surface	,	weight	2.35	lbs. / ft. V	Vall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Ste		3 Stainless Steel		5 Fiberglass		8 RMP (SR)	11 other (specify	-	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCIPEEN OF PEPEORATION OPENING APE: 6 Concrete tile 9 ABS 11 None (open hole)									
		RFORATION OP			uzed wrapped			11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 30 ft. to 80 ft., From ft. to ft.									
from					ft. to	ft., From ft., From	ft. to	ft.	
	GRAV	EL PACK INTER			ft. to 80		ft. to	ft.	
from ft. to ft., From ft. to ft 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
What is the nearest source of possible contamination:				n, rrom			ft. From k pens 14 /	bandon water well	
1 Septie tank 4 Lateral lines				7 Pit privy		11 Fuel sto		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertiliz	- 15	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage plt 9 Feedyard 13 Insecticide storage None Apparent									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0	4	topsoil							
4	18	clay					·		
18	70	shale							
70	80	limesto	ne						
			,						
	<u> </u>								
	1								
	1								
· · · · · · · · · · · · · · · · · · ·	<u> </u>		······································						
<u> </u>	t								
	<u> </u>		······································						
	1								
⁷ CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Under the business name of Harp Well & Pump Service. Inc. by (signature)									
Jane Frederick									
fane Trederick									