

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NW 1/4 NW 1/4 NW 1/4		Section Number 19	Township Number T 27 S		Range Number R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 6411 EAST CENTRAL; WICHITA, KS								
2 WATER WELL OWNER: D.M. CARNEY RR#, St. Address, Box # : 8100 E 22ND ST. NORTH City, State, ZIP Code : WICHITA KS 67226				Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 20.5 ft. ELEVATION: APPROX. 1380 MSL Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 7.51 ft. below land surface measured on mo/day/yr 11-9-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 10.5 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 0 in. weight lbs./ft. Wall thickness or gauge No. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20.5 ft. to 10.5 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20.5 ft. to 7.8 ft. From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 7.8 ft. to 2.7 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? WEST How many feet? 20 ft								
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS						
0	0.65	FT ASPHALT/CONCRETE						
0.65	5	CLAY; OLIVE BLACK; DRY						
5	11.5	CLAY; SANDY; MOD. BROWN						
11.5	12.3	GRAVEL LAYER; WET						
12.3	15.5	CLAY; MOD. YELLOWISH BROWN						
15.5	16	GRADES TO WEATHERED SHALE; DRY						
	20.5	TOTAL DEPTH OF BORING						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-9-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 524 This Water Well Record was completed on (mo/day/yr) 11-20-95 under the business name of Allied Laboratories by (signature) Robert B. Braum								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.								