

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NW 1/4 NW 1/4 NW 1/4	Section Number 18	Township Number T 27 S	Range Number R 2 EW
Distance and direction from nearest town or city street address of well if located within city? 6327 E. 13th St., Wichita, Ks.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Amoco Oil Co. 8700 Indian Creek Pkwy Suite 190 Overland Park, Ks. 66210 Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 20'3" ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 8'4" ft. below land surface measured on mo/day/yr 1-3-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" in. to 20'3" ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X Blank casing diameter 2.375 in. to 5' ft., Dia in. to ft., Dia in. to SDR 13 ft. Casing height above land surface Flush Ht. in., weight lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
		SCREEN-PERFORATED INTERVALS: From 20' ft. to 5' ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20' ft. to 4' ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4' ft. to 3' ft. From 3' ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage Father 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? West Northwest How many feet? 30'					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	.50	Asphalt			
.50	8	Dk brn clay w/ few ls.rx. gravel frag., dry to moist, mod. odor, Green-gray clay mottling at 4 1/2'.			
8	10	Gray green clay to shaley clay w/ dk gray bands at 8', moist, mod. to strong odor, firm to stiff.			
10	12.25	Med brn-orange red shaley clay, tight, faint odor, mottled, caliche, firm to stiff.			
12.25	15	Greenish gray clayey shale, caliche, faint to no odor, dry, firm.			
15	20'3	Lt brn-olive clayey shale, dry, firm, no odor, highly weathered shale w/ caliche.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) Constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-2-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 1-9-96 under the business name of JB Environmental Drilling by (signature) James Becker					