

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick		NE 1/4 NW 1/4 NE 1/4		36		T 27 S		R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city?									
1630 S. Tamarisk Court Wichita, Kansas									
2 WATER WELL OWNER:		PAGE, Gerrild				Board of Agriculture, Division of Water Resource			
RR#, ST. ADDRESS, BOX #:		1630 S. Tamarisk Court				Application Number:			
CITY, STATE, ZIP CODE:		Wichita, Kansas 67230							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 63 ft. ELEVATION:							
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.							
		WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON 04/23/1996							
		Pump test data: Well water was 1 ft. after 2 hours pumping 3 gpm							
		Est. Yield 12 gpm: Well water was 1 ft. after 2 hours pumping 3 gpm							
		Bore Hole Diameter 12 in. to 63 ft. and 1 in. to 1 ft.							
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No									
5 TYPE OF CASING USED:									
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued ☒ Clamped ☒	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (Specify below)		Welded	
				7 Fiberglass		SDR-26		Threaded	
Blank casing Diameter 5 in. to 24 ft., Dia		in. to 24 ft., Dia		in. to 24 ft., Dia		in. to 24 ft., Dia		in. to 24 ft., Dia	
Casing height above land surface 12 in., weight 2.35 lbs. / ft.		in. to 24 ft., Dia		in. to 24 ft., Dia		in. to 24 ft., Dia		in. to 24 ft., Dia	
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVALS:		1 Continuous slot 3 Mill slot 6 Wire wrapped 7 Torch cut							
GRAVEL PACK INTERVALS:		1 Continuous slot 3 Mill slot 6 Wire wrapped 7 Torch cut							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 4 ft. to 24 ft. From 4 ft. to 24 ft. From 4 ft. to 24 ft. From 4 ft. to 24 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? West How many feet? 20									
LITHOLOGIC LOG									
FROM	TO	LITHOLOGIC LOG							
0	2	topsoil							
2	10	clay							
10	55	shale							
55	63	limestone							
PLUGGING INTERVALS									
FROM	TO	PLUGGING INTERVALS							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 04/23/1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/24/96 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>									