LOCAT	TON OF W	TED WELL.	FRACTION	Wat	er Well Reco	ord Form WWC-	Section Number	T = 1. V.	Down Name
			. NE		CB		Township Number	Range Number	
SECQWICK SE 1/4 Distance and direction frem nearest town or city street address of well if locate						SE 1/4	10	T 27 s	R 2E EW
12719 Castlewood Court Wichita, Kansas Water Wellowner: WILLAIMS, George									
12/19 Castlewood Coult									
	IN SECTION		Depth(s) groun			80 1	ft. ELI	EVATION: 2 ft.	3 ft.
l t		-}				_			3 ft. 06/26/1996
'	NW	NE	est. Yield			water was	ft. ft.	•	
w Mile			sc. Tielu lore Hole Diamet	gpm: er 12	in.		rt. ft.	after hours pum	
Į ≅ w		, - L	VELL WATER T			to 80 5 Public wate	_	and in. 8 Air conditioning 11 Is	to ft. njection well
			1 Domestic	3 Feedl		6 Oil field w		•	Other (Specify below)
	- sw		2 Irrigation	4 Indus		7 Lawn and		10 Monitoring well	diei (opeeny belon)
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was								o/day/yr samnle was
S submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Steel		3 RMP (SR)			stos-Cem		Other (Specify b		Velded
2 PVC		4 ABS		7 Fiber	glass		DR-26	•	'hreaded
Blank cas	_ sing Diam	eter 5 i	in. to 35	ft. ,	Dia	in		ft., Dia in.	to ft.
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214									
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify))
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN	OR PEI	RFORATION OPEN	ING ARE:		5 Gau	ızed wrapped		8 Saw cut	11 None (open hole)
1 Contin	ous slot	3 Mill slot			6 Wir	e wrapped		9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 35 ft. to 80 ft., From ft. to ft.									
from					ft. to		ft., From	ft. to	ft.
GRAVEL PACK INTERVALS: from 24				24	ft. to 80		ft., Fron		ft.
<u> </u>			from		f	t. to	ft., Fron	n ft. to	ft
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 4 ft. to 24					ft. From f		to	ft. From	ft. to ft.
What is the nearest source of possible contamination:			_	# PM		10 Livesto		14 Abandon water well	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel st	130	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				ewage lag	oon		aldo atomaso	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent									Apparent
Direction from well? How many feet?									
FROM O	<u>TO</u>	topsoil	THOLOGIC LO	XG		FROM	TO	PLUGGING INTE	RVALS
	18	clay					11.000		
	70	shale			TO LU .				
	80	limestone	.						
		11110000	<u> </u>					The state of the s	
								9 48. ·	1 1000000000000000000000000000000000000
								7.741.34.	
				10/12/2					
								//-WI-WI-	
								The state of the s	
								The state of the s	
			7.20						
7 CON	TRACTO	R'S OR LANDOWNER'S	S CERTIFICATION:	This water	well was	(1) construc	ted (2) reconstr	ucted or (3) plugged under n	ov jurisdiction and
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
Well Contractor's License No23.5									
Under the business name of Harp. Well & Pump. Service									
			_				, , , ,	Todd. S	Haso