

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE 1/4 SW 1/4 NW 1/4	12	T 27 S	R 2 EW
Distance and direction from nearest town or city street address of well if located within city? From the NW corner of Sec. 12, 1433' South; 750' East					
2 WATER WELL OWNER: David E Wittwer					
RR#, St. Address, Box #: 3219 West May PO BOX 9444					
City, State, ZIP Code: Wichita, Ks. 67277-0444					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 69 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 38 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 21.9" ft. below land surface measured on mo/day/yr 6/28/96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield .8 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter .10 in. to .69 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter .5 in. to .25 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface .30 in., weight 160 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 3 Mill slot 6 Wire wrapped 9 Drilled holes					
4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From .25 ft. to .69 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From .23 ft. to .69 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From .23 ft. to .19 (2) ft., From .19 ft. to .3 (3) ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? South How many feet? 300+					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0.0 9.0 Brownish yellow shale					
9.0 38.0 Yellow gray shale with thin limestone stringers					
38.0 67.0 Yellow gray shale with thin interbedded clay layers					
67.0 69.0 Gray shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/28/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 279 This Water Well Record was completed on (mo/day/yr) 7/6/96 under the business name of Fudge Drilling by (signature) Michael R. Fudge					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					