

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW ¼ NE ¼ NW ¼		12		T 27 S		R 2 E/W	
Distance and direction from nearest town or city street address of well if located within city? From the NW corner of Sec. 12, 1824 E., 834 S.									
2 WATER WELL OWNER: Shane Prill									
RR#, St. Address, Box #: 2353 N. Stoneybrook Ct.									
City, State, ZIP Code: Wichita, Ks. 67226									
Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 19.5 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 11.5 ft. below land surface measured on mo/day/yr 1/17/96							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield 1.5+ gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 1.0 in. to 10.0 ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)							
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded									
Blank casing diameter 5 in. to 18 ft. Dia in. to ft. lbs./ft. Wall thickness or gauge No.									
Casing height above land surface 18 in. weight 160									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 100 ft. to 18 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 100 ft. to 17 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout intervals: From 17 ft. to 16 (2) ft. From 16 ft. to 3 (3) ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well? To be const'd per Sedgwick Co. Code How many feet?									
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS			
0.0	2.0	Top Soil							
2.0	9.0	Yellow gray shale							
9.0	19.0	Brownish gray clay							
19.0	39.0	Yellow gray shale							
39.0	42.5	Lighter yellow gray shale							
42.5	62.0	Yellow gray shale							
62.0	100.0	Gray shale with interbedded thin clay							
100.0	108.0	Gray shale with thin gypsum layers (Plugged back to 100')							

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **1/17/96** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **279** This Water Well Record was completed on (mo/day/yr) **1/25/96** under the business name of **Fudge Drilling** by (signature) *Michael R. Fudge*