


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW/4 SW/4 NW/4	Section Number 21	Township Number T 27 S	Range Number R 2 E																																																																														
Distance and direction from nearest town or city street address of well if located within city? 9709 EAST CENTRAL WICHITA, KANSAS																																																																																			
2 WATER WELL OWNER: RAYMEON AIRCRAFT COMPANY RR#, St. Address, Box #: 9709 EAST CENTRAL City, State, ZIP Code: WICHITA, KANSAS 67206			Board of Agriculture, Division of Water Resources Application Number:																																																																																
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 7 1/4 in. to 40 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below) Dual Extraction Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr samples submitted Water Well Disinfected? Yes No																																																																																	
5 TYPE OF BLANK CASING USED: 1 Steel Stainless 2 PVC Blank casing diameter 2 1/2 in. to 10 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 0 in., weight 4.185 lbs./ft. Wall thickness or gauge No. 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded X																																																																																			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Stainless steel 4 Galvanized steel 3 Mill slot 4 Key punched 5 Fiberglass 6 Concrete tile 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 RMP (SR) 9 ABS 8 Saw cut 9 Drilled holes 10 Other (specify) 11 Other (specify) 12 None used (open hole) 11 None (open hole)																																																																																			
SCREEN-PERFORATED INTERVALS: From 40 ft. to 10 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 40 ft. to 8 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																																			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From ft. to ft., From 0 ft. to 1 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? How many feet?																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr><td>0</td><td>1.8</td><td>Concrete</td><td></td><td></td><td></td></tr> <tr><td>1.8</td><td>3.0</td><td>Fill MATERIALS</td><td></td><td></td><td></td></tr> <tr><td>3</td><td>5</td><td>SILTY CLAY, dk BROWN</td><td></td><td></td><td></td></tr> <tr><td>5</td><td>6</td><td>CLAYEY SILT, SLIGHTLY DAMP</td><td></td><td></td><td></td></tr> <tr><td>6</td><td>12.5</td><td>SILTY CLAY</td><td></td><td></td><td></td></tr> <tr><td>12.5</td><td>18</td><td>SILTY CLAY, OLIVE GREEN</td><td></td><td></td><td></td></tr> <tr><td>18</td><td>18.2</td><td>SAME AS ABOVE, SLIGHTLY DAMP</td><td></td><td></td><td></td></tr> <tr><td>18.2</td><td>24</td><td>SILTY CLAY, OLIVE GREEN</td><td></td><td></td><td></td></tr> <tr><td>24</td><td>26</td><td>Gypsum Hard weathered</td><td></td><td></td><td></td></tr> <tr><td>26</td><td>28.5</td><td>Silty Clay stiff olive green wet</td><td></td><td></td><td></td></tr> <tr><td>28.5</td><td>35'</td><td>Silty Shale, dark blue to black highly weathered</td><td></td><td></td><td></td></tr> <tr><td>35'</td><td>40'</td><td>SAME AS ABOVE</td><td></td><td></td><td></td></tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	1.8	Concrete				1.8	3.0	Fill MATERIALS				3	5	SILTY CLAY, dk BROWN				5	6	CLAYEY SILT, SLIGHTLY DAMP				6	12.5	SILTY CLAY				12.5	18	SILTY CLAY, OLIVE GREEN				18	18.2	SAME AS ABOVE, SLIGHTLY DAMP				18.2	24	SILTY CLAY, OLIVE GREEN				24	26	Gypsum Hard weathered				26	28.5	Silty Clay stiff olive green wet				28.5	35'	Silty Shale, dark blue to black highly weathered				35'	40'	SAME AS ABOVE			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																														
0	1.8	Concrete																																																																																	
1.8	3.0	Fill MATERIALS																																																																																	
3	5	SILTY CLAY, dk BROWN																																																																																	
5	6	CLAYEY SILT, SLIGHTLY DAMP																																																																																	
6	12.5	SILTY CLAY																																																																																	
12.5	18	SILTY CLAY, OLIVE GREEN																																																																																	
18	18.2	SAME AS ABOVE, SLIGHTLY DAMP																																																																																	
18.2	24	SILTY CLAY, OLIVE GREEN																																																																																	
24	26	Gypsum Hard weathered																																																																																	
26	28.5	Silty Clay stiff olive green wet																																																																																	
28.5	35'	Silty Shale, dark blue to black highly weathered																																																																																	
35'	40'	SAME AS ABOVE																																																																																	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-19-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 9-6-96 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature) <i>[Signature]</i>																																																																																			