

QT376R

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: <u>Sedgwick</u>		<u>SW 1/4 SW 1/4 SW 1/4</u>		<u>32</u>		<u>T 27 S</u>		<u>R 2 E</u>			
Distance and direction from nearest town or city street address of well if located within city? <u>2106 S. Rock Rd Wichita, KS</u>											
2 WATER WELL OWNER:					Application Number:						
RR#, St. Address, Box # : <u>GT Corp. 376R</u> <u>PO Box 3475</u>					<u>mw6 420871246</u>						
City, State, ZIP Code : <u>Tulsa, OK 74101</u>					Board of Agriculture, Division of Water Resources						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL: <u>15</u> ft. ELEVATION: <u>~11</u> ft.						
					Depth(s) Groundwater Encountered 1. <u>11</u> ft. 2. <u>15</u> ft. 3. <u>15</u> ft.						
					WELL'S STATIC WATER LEVEL <u>15</u> ft. below land surface measured on mo/day/yr						
					Pump test data: Well water was <u>15</u> ft. after <u>15</u> hours pumping <u>15</u> gpm						
					Est. Yield <u>15</u> gpm: Well water was <u>15</u> ft. after <u>15</u> hours pumping <u>15</u> gpm						
Bore Hole Diameter <u>15</u> in. to <u>15</u> ft. and <u>15</u> in. to <u>15</u> ft.					WELL WATER TO BE USED AS:						
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					5 Public water supply 8 Air conditioning 11 Injection well						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> If yes, mo/day/yr sample was submitted					Water Well Disinfected? Yes <u>No</u>						
5 TYPE OF BLANK CASING USED:					CASING JOINTS: Glued <u>Clamped</u>						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile					6 Asbestos-Cement 9 Other (specify below) <u>Welded</u>						
2 PVC 4 ABS 7 Fiberglass <u>Threaded</u>					Blank casing diameter <u>2</u> in. to <u>5</u> ft. Dia. <u>15</u> in. to <u>15</u> ft. Dia. <u>15</u> in. to <u>15</u> ft.						
Casing height above land surface <u>0</u> in. weight <u>15</u> lbs./ft. Wall thickness or gauge No. <u>15</u>					TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:					5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From <u>5</u> ft. to <u>15</u> ft. From <u>5</u> ft. to <u>15</u> ft.					GRAVEL PACK INTERVALS: From <u>4</u> ft. to <u>15</u> ft. From <u>4</u> ft. to <u>15</u> ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					Grout Intervals: From <u>0</u> ft. to <u>2.5</u> ft. From <u>2.5</u> ft. to <u>4</u> ft.						
What is the nearest source of possible contamination:					10 Livestock pens 14 Abandoned water well						
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage <u>USTS</u>					Direction from well? <u>USTS</u>						
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		2		Topsoil		0		2			
5		7		Clay, olive green-gray mottled		5		7			
10		12		Clay, olive green-gray mottled, red at 11.75'		10		12			
Flushmount waiver by D. Taylor											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3/28/97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>483</u> This Water Well Record was completed on (mo/day/yr) <u>4/25/97</u> under the business name of <u>T.E.S.T.</u> by (signature) <u>Bob Robinson</u>											