Liona	TION OF THE	TER WELL:	FRACTION	Water Well Reco	ord Form WWC-5	KSA 82a-1212		
Ĺ						Section Number	Township Number	Range Number
Sedgwick SW 1/4				SW 1/4	11	T 27 s	R 2E E/W	
Distance and direction frem nearest town or city street address of well if located within city?								
1546 Rocky Creek Road Wichita, Kansas								
WATER WELL OWNER: MALONE, Mark RR#, ST. ADRESS, BOX#: 1546 Rocky Creek Road Board of Agriculture, Divivsion of Water Resource								
		-5-0			A ROAG			
$\overline{}$	STATE, ZIP	OCATION WITH 4	ita, Kansa		0.0	. FI	Application Numbe	r:
	IN SECTION		DEPTH OF COM Depth(s) groundwa		82 1	ft. EL ft.	LEVATION: 2 ft.	3 ft.
l +		- 	WELL'S STATIC W		_		URFACE MEASURED ON mo/day/yr	03/03/1999
1			VELL S STATIC W. Pump test		water was	ft.	after hours pum	
l '	NW	····NE	Est. Yield		water was	ft.	after hours pum	
Mije M		1 1 1	Bore Hole Diameter	12 in.	to 82	ft.	and in.	to ft.
\ \frac{1}{2} \ \text{W}			WELL WATER TO E		5 Public water			njection well
Ι.	X sw		1 Domestic	3 Feedlot	6 Oil field wa		9 Dewatering 12 C	Other (Specify below)
	l sw		2 Irrigation	4 Industrial	7 Lawn and g	arden only	10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample wa							o/day/yr sample was
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel	l	3 RMP (SR)		6 Asbestos-Cem	ent 9	Other (Specify	below) V	Velded
2 PVC	ı	4 ABS		7 Fiberglass	S	DR-26	Т	hreaded
Blank ca	sing Diam	eter 5 i	in. to 42	ft., Dia	in.	to	ft., Dia in.	to ft.
	-	e land surface 12		weight		lbs. / ft.	Wall thickness or gauge No.	.214
i		N OR PERFORATI	ION MATERIAL:	5 Fiberglass		PVC DMD (SD)	10 Asbestos-ceme	
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
							11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 42 ft. to 82 ft., From ft. to ft.								
from					t. to	ft., Fro		ft.
	GRAVI	EL PACK INTERVA			ft. to 82	ft., Fro		ft.
from ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Crout Intervals: From A 8 to 24								
Grout Intervals: From 4 ft. to 24 What is the nearest source of possible contamination:				ft. From ft. to		to 10 Livest	ft. From tock pens 14 A	ft. to ft. bandon water well
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel s	4	Dil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertil		Other (specify below)
3 Water	tight sewe	-		9 Feedyard	13 Insecticide storage			
Direction from well? West How many feet? 100								
FROM	TO	L	ITHOLOGIC LOG		FROM	то	PLUGGING INTE	RVALS
	4	topsoil						
4	20	clay						
	75	shale				ļ. ļ		
75	82	limestone	9					
						+		
					-			
						1		
							AND THE THE STATE OF THE STATE	******
						-		
7 CON	/TD : C= 0	Dig on -			(4)	ad (0)	trusted or /2) plumas dum des	ny juriediation and
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Was completed on (mo/day/year)								
Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp								
Unider	tne busir	iess name of Akma	r.trx.e.+++&	£'\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	······································	rx by (sig	mature) ~ , , ^	0.0