				Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCA		ATER WELL:	FRACTION			Section Number	Township Number	Range Number
	Sedgr	wick	NW 1/	4 SE 1/4 N	W 1/4	8	т 27 s	R 2E E/W
Distance	and direction	frem nearest town or ci	ty street address of well t	f located within city?				<u> </u>
1906 Saddle Creek Wichita, Kansas								
WATER WELL OWNER: LAHAM, Dr. Jerome								
RR#, ST. ADRESS, BOX#: 1906 Saddle Creek  Board of Agriculture, Divivsion of Water Resource								
CITY	, STATE, ZII		hita, Kan				Application Number	r:
LOCA	TE WELL'S	LOCATION WITH		OMPLETED WELL	55	ft. ELEV	VATION:	
	" IN SECTIO		Ш	dwater Encountered	1	ft.	2 ft.	3 ft.
l t			- 175	WATER LEVEL 8			FACE MEASURED ON mo/day/yr	04/12/1999
					ater was		fter hours pum	
Ι'	NW	NE	Est. Yield		ater was		fter hours pun	. 6
1 Mile			Bore Hole Diamete	01	to 55	ft.	and in.	ping gpm to ft.
\ \frac{1}{2} M		E	WELL WATER T	<del></del>	Public water			njection well
1			1 Domestic		Oil field wat		•	Other (Specify below)
1	SW	SE	2 Irrigation		Lawn and ga		Monitoring well	suiti (speelly below)
1 1				•			•	o/dov/rm comple wee
'		S	submitted	acteriological sample sub	mitted to Dej		r Well Disinfected? Yes	io/day/yr sample was
5 TY	PE OF CA	SING USED:	эиминиси					
1 Stee		3 RMP (SR)		5 Wrought iron 6 Asbestos-Cemen		Concrete tile		dued X Clamped
2 PV		4 ABS		7 Fiberglass	-	Other (Specify bel	•	Velded `hreaded
				J		DR-26		-
	asing Diam	-	in. to 25	ft., Dia	in.		ft., Dia in.	to ft.
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Ste		3 Stainless Steel	TION WATERIAL	5 Fiberglass	_	RMP (SR)	11 other (specify	
2 Brass 4 Galvanized steel 6 Concrete tile						9 ABS 12 None used (open hole)		
						O.C		
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed 1 Continuous slot 3 Mill slot 6 Wire w						ppeu		
1		3 Mill sl		6 Wire v				
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREE	N-PERFO	RATION INTERV	VALS: from 2	25 ft. 1	to 55	ft., From	ft. to	ft.
from ft. to						ft., From		ft.
_					to 55	ft., From	ft. to	ft.
		4 37 - 4	from	ft.		ft., From	ft. to	ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to								
What is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines  7 Pit privy						10 Livestock pens		bandon water well
l a						11 Fuel storage		Oil well/Gas well
2 Sewer lines 5 Cess pooi 8 Sewage lagoo					n	12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		
" Tecuyaru								
Direction from well?   West   How many feet?   100								
			LITHOLOGIC LO	OG .	FROM	ТО	PLUGGING INTE	RVALS
0	10	topsoil						
4 10	35	clay			<u> </u>			
		shale						
35	55	limestor	ie					
						-		
					ļ	<del> </del>		
-								
	-					-		
<u> </u>	<u></u>						<u></u>	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well (	Contracto	r's License No	236	This Water Well Re	cord was co	mpleted on (mo	0/4/1	
Under the business name of HarpWell&PumpServiceInc by (signature)								
							Todd X	. Harp