, LOCATION OF WATER WELL:	FRACTION	water Well Record	Form WWC-5	Section Number	T	DN
	1				Township Number	Range Number
Sedgwick	NW 1/4		E 1/4	10	т 27 s	R 2E EAW
Distance and direction frem nearest town or city street address of well if located within city?						
12527 Tallowood		Wic	hita,	Kansas		
L.—I	AN, Stan	منم محد	_			
RR#, ST. ADRESS, BOX#: 12527 Tallowood Stepien Board of Agriculture, Divivsion of Water Resource						
CITY, STATE, ZIP CODE: Wichi	ta, Kansa	s			Application Number	:
LOCATE WELL'S LOCATION WITH 4	DEPTH OF COM	APLETED WELL	83	ft. ELEV	ATION:	
AN "X" IN SECTION BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.
	ELL'S STATIC W	ATER LEVEL 30	) FT.	BELOW LAND SURF	ACE MEASURED ON mo/day/yr	04/12/1999
NWNE	Pump test	data: Well w	vater was	ft. af	ter hours pump	ping gpm
Est	. Yield	gpm: Well v	water was	ft. a	fter hours pump	
W X E Bo	e Hole Diameter	<b>12</b> in.	to 83	ft.	and in.	to ft.
= "	LL WATER TO I	BE USED AS:	5 Public water	r supply 8	Air conditioning 11 In	jection well
sw	1 Domestic	3 Feedlot	6 Oil field wa	ter supply 9	Dewatering 12 O	ther (Specify below)
	2 Irrigation	4 Industrial	7 Lawn and g	arden only 10	Monitoring well	
	s a chemical/bacte	riological sample su	bmitted to De	partment? Yes	No X ; If yes, me	o/day/yr sample was
S submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED:		5 Wrought iron	8	Concrete tile		ued X Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cemer		Other (Specify bel	0.	elded
2 PVC 4 ABS		7 Fiberglass		DR-26	•	hreaded
Blank casing Diameter 5 in.	to 43					
Casing height above land surface 12		ft., Dia	in. 2 E		ft. , Dia in. 'all thickness or gauge No.	to ft.
TYPE OF SCREEN OR PERFORATION	in. , N MATERIAL:	weight 2		PVC	10 As bestos-ceme	.214
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify)	
2 Brass 4 Galvanized steel		6 Concrete tile		ABS	12 None used (ope	
SCREEN OR PERFORATION OPENII	IC ADE.			ADS	8 Saw cut	11 None (open hole)
4	IG ARE:		ed wrapped		9 Drilled holes	11 None (open note)
2 Louvened shutton A Venumbed						
/ Torch cut						
SCREEN-PERFORATION INTERVAL	S: from 43	ft.	to 83	ft., From	ft. to	ft.
	from	ft.	to	ft., From	ft. to	ft.
GRAVEL PACK INTERVAL	S: from 24	ft.	to 83	ft., From	ft. to	ft.
	from	<u>ft.</u>		ft., From	ft. to	ft
6 GROUT MATERIAL: 1 Neat cem		ement grout	3 Ber	tonite	4 Other bentonite	hole plug
	to 24	ft. From	ft.		ft. From	ft. to ft.
What is the nearest source of possible contamination:		7 Tr.		10 Livestock		oandon water well
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel stor	a 120	il well/Gas well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilize		ther (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? East			-		How many feet? 60	
	HOLOGIC LOG		FROM	TO	PLUGGING INTER	VALS
0 4 topsoil						
4 40 clay			-	ļ		7818
40 83 shale				ļ		
				ļ		
			<u> </u>			
				ļ		
			ļ	ļ		
			ļ			
				ļ		
						100
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and						
was completed on (mo/day/year)						
Well Contractor's License No236						
Under the business name of Harp Well & Pump Service. Inc. by (signature)						
					Todd &	. Harp