Iroca	TION OF WA	TER WELL:	FRACTION	Water	Well Record	Form WWC-5				
					ara		Section Number		Kai	nge Number
	Sedgy		NW 1/4		1/4 SW	1/4	11	T 27 s	R	2E _{E/W}
Distance and direction frem nearest town or city street address of well if located within city?										
1709 Rocky Creek Ct. Wichita, Kansas WATER WELL OWNER: KINGREY, David										
RR#, ST. ADRESS, BOX#: 1709 Rocky Creek Ct. Board of Agriculture, Divivsion of Water Resource										ater Resource
CITY, STATE, ZIP CODE: Wichita, Kansas								Application Number:		
LOCAT	E WELL'S L	OCATION WITH	4 DEPTH OF C		WELL	70	ft. El	LEVATION:		
AN "X"	IN SECTIO	N BOX: N	Depth(s) groun			1	ft.	2 ft.	3	ft.
1 1			WELL'S STATIC	WATER LEV	EL 20	FT.	BELOW LAND S	SURFACE MEASURED ON mo/da	y/yr 05/2	26/1999
	NW	NE	Pump (test data:	Well wat	er was	ft.	after hours	pumping	gpm
يو			Est. Yield	gpm:	Well wat		ft.	after hours	pumping	gpm
Mile M		E	Bore Hole Diamete		in. to		ft.	and	in. to	ft.
-			WELL WATER TO			ublic wate		8 Air conditioning	11 Injection w	
1 1	sw	ste	1 Domestic	3 Feedlot 4 Industr			ter supply arden only	9 Dewatering	12 Other (Spe	city below)
			2 Irrigation				•	10 Monitoring well		l
*		S	Was a chemical/ba submitted	cteriological s	ample subm	itted to De	-		yes, mo/day/yr s: Yes X	-
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Steel		3 RMP (SR)			s-Cement		Other (Specify		Welded	Clampeu
2 PVC	!	4 ABS		7 Fibergl	ass		DR-26	,	Threaded	
Blank ca	_ sing Diam	eter 5	in. to 30	ft.,	Dia	in.	to	ft., Dia	in. to	ft.
Casing h	eight abov	e land surface	L 2 նո	•	eight 2.3	35	lbs. / ft.	Wall thickness or gauge N		.214
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 As bestos-cement										
1 Stee		3 Stainless Steel		5 Fibergla			RMP (SR)	11 other (s	pecify)	
2 Brass 4 Galvanized steel 6 Concrete tile							O ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:						wrapped		8 Saw cut 11 None (open hole)		
1 Contir		3 Mill sl			6 Wire wr	apped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREE	N-PERFO	RATION INTERV		30	ft. to	70	ft., Fro	om f	t. to	ft.
GRAVEL PACK INTERVALS: from 24					ft. to		ft., Fro		L to	ft.
	GRAVI	EL PACK INTER	24	ft. to 70		ft., Fr	_	ft. to	ft.	
from ft. to ft., From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Crout Intervals: From A 8 40 2 A										ft.
What is the nearest source of possible contamination:				11	in Itom			tock pens	14 Abandon water well	
1 Septic tank 4 Lateral lines				7 Pit	7 Pit privy		11 Fuel	storage	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sew	8 Sewage lagoon			ilizer storage	16 Other (specify below)	
3 Water	rtight sewe	er lines 6 Seep	age pit	9 Fee	dyard		13 Insecticide storage			
Direction from well? East How many feet? 90										
FROM	TO		LITHOLOGIC LO	<u>G</u>		FROM	ТО	PLUGGING I	<u>NTERVALS</u>	
0 3	3 9	topsoil clay								
9	70	grey sha	مام							
	′	grey sine	116				1			
					-					
<u> </u>							1			
							1			
							+ +			
7 CON			·				-1 (6)	44-1 (4)	alon was to 1 · 4	otlan
I COL								tructed, or (3) plugged ur the best of my knowledg		
Was co	ontractor	on (mo/day/year ''s License No	,	This Wate	an r Well Rece	ord was c	ompleted on i	(mo/day/yr)Q.5	/27/99	.u.13Q3
Under	the busir	ness name of H	arp Well &	Pump S	Servic	e. II	າດ by (sig	gnature)		
Under the business name of Harp Well & Pump Service. Inc by (signature) Todd & Harp										