

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NE</u> <u>NE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	<u>14</u>	T <u>27</u> S	R <u>2</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>660 Preston Trail, Wichita</u>					
2 WATER WELL OWNER: <u>Grant Nutter</u>					
RR#, St. Address, Box #: <u>660 Preston Trail</u>					
City, State, ZIP Code: <u>Wichita, KS 67230</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>89</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>83</u> ft. 2. <u>83</u> ft. 3. <u>83</u> ft.			
		WELL'S STATIC WATER LEVEL <u>83</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was <u>25</u> ft. after <u>25</u> hours pumping <u>25</u> gpm			
		Est. Yield <u>25</u> gpm: Well water was <u>25</u> ft. after <u>25</u> hours pumping <u>25</u> gpm			
		Bore Hole Diameter <u>10</u> in. to <u>10</u> ft., and <u>10</u> in. to <u>10</u> ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial <u>7</u> Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>Clamped</u>					
<u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
7 Fiberglass Threaded					
Blank casing diameter <u>6</u> in. to <u>2</u> ft., Dia <u>5</u> in. to <u>69</u> ft., Dia <u>69</u> in. to <u>69</u> ft.					
Casing height above land surface <u>18</u> in., weight <u>18</u> lbs./ft. Wall thickness or gauge No. <u>18</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot <u>2 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>69</u> ft. to <u>89</u> ft., From <u>69</u> ft. to <u>89</u> ft.					
GRAVEL PACK INTERVALS: From <u>22</u> ft. to <u>89</u> ft., From <u>22</u> ft. to <u>89</u> ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>2</u> ft. to <u>22</u> ft., From <u>22</u> ft. to <u>22</u> ft., From <u>22</u> ft. to <u>22</u> ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage <u>16 Other (specify below)</u>					
<u>Pond</u>					
Direction from well? <u>South East</u> How many feet? <u>100</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	8	Yellow Clay			
8	20	Green Shale			
20	40	Light Gray Shale			
40	46	Broken Lime			
46	57	Shale / Brown / Gray			
57	83	Gray shale			
83	89	Lime / Broken			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-5-98</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>464</u> This Water Well Record was completed on (mo/day/yr) <u>12-5-98</u>					
under the business name of <u>Water Well Services, Inc.</u> by (signature) <u>[Signature]</u>					